

Conductive Plastic Rotative Transducer Elements (KIT)



The RMF is a precision rotative motion transducer designed for easy mounting into your equipment.

FEATURES

- Reduced dimensions and weight
- Cost effective solution
- Easy mounting
- Model dedicated to custom design requirements

It is made of 2 parts:

- A sensing element in a housing
- A wiper

On request, their shapes and sizes can be custom-designed to fit your equipment.

ELECTRICAL SPECIFICATIONS	
Theoretical Electrical Angle (TEA = E)	AEA - 2°
Independent Linearity over TEA On Request (Depending on Size)	A ≤ ± 1 %; B ≤ ± 0.5 % C ≤ ± 0.25 %; D ≤ ± 0.1 % down to E ≤ ± 0.05 %
Actual Electrical Angle (AEA)	340 ± 3° or 350 ± 2° according to the model
Total Resistance R _T On Request	1 kΩ, 2 kΩ, 5 kΩ, 10 kΩ other values
Total Resistance Tolerance at 20 °C	± 20 %
Repeatability	< 0.01 %
Wiper Current	1 mA max. continuous, recommended: a few μA
Load Impedance	1000 times R _T minimum
Insulation Resistance	> 1000 MΩ 500 V _{DC}
Dielectric Strength	> 500 V _{RMS} at 50 Hz

MECHANICAL SPECIFICATIONS	
Mechanical Angle MA	360° continuous
Substrate	Thermosetting resin
Termination On Request	Turrets wires, cables
Wiper	Multi-finger precious metal alloy

PERFORMANCE	
Life	25 million cycles typical
Temperature Limits	- 30 °C at + 85 °C



EXAMPLES OF SPECIAL DESIGNS



ORDERING INFORMATION/DESCRIPTION					
KIT	RM	F	116	D	103
SERIES	MODEL	TYPE	SIZE	LINEARITY	RESISTANCE
		F: Plastic S: Serigraphy		A: $\leq \pm 1\%$ B: $\leq \pm 0.5\%$ C: $\leq \pm 0.25\%$ D: $\leq \pm 0.1\%$ E: $\leq \pm 0.05\%$	First 2 digits are significant numbers Third indicates number of zeros

SAP PART NUMBERING GUIDELINES				
RMS	200	A	502	
MODEL	SIZE	LINEARITY	OHMIC VALUE	



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.