



PLL Product Specification

Model: PLL250-941(Y) **Rev:** P4 **Date:** 9/1/2006
Customer: SIRENZA MICRODEVICES, INC. **AppNote:** 113 Option 007000
Operating Temperature Range: (-10 ° to 85 ° C)

Pb RoHS Compliant
To order models as RoHS Compliant add "Y" suffix to base model number.

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	920		960	MHz	X	
Step Size -		200		kHz	X	
Settling Time - to within 5 deg.		0.4	0.45	mSec		
Output Power:						
RF Switch ON	-1	2	5	dBm	X	
RF Switch OFF		-58	-50	dBm	X	
Output Phase Noise:						
1 kHz		-92	-88	dBc/Hz		
100 kHz		-125	-113	dBc/Hz		
200 kHz		-133	-123	dBc/Hz		
400 kHz		-138	-135	dBc/Hz	X	
1800 kHz		-155	-150	dBc/Hz		
3000 kHz		-158	-155	dBc/Hz		
Power Supply:						
VCC 1: VCO, PLL CP	5.75	6	6.25	Volts	X	
VCC 2: Amp	4.75	5	5.25	Volts	X	
VCC 3: PLL IC,Switch	3.15	3.3	3.45	Volts	X	
Supply Current:						
VCC 1		12	40	mA	X	
VCC 2		45	80	mA		
VCC 3		10	15	mA		
Spurious Product:						
200 kHz		-92	-80	dBc	X	
400 kHz		-102	-90	dBc		
1800 kHz		-117	-100	dBc		
non-harmonic			-100	dBc		
Reference Feedthrough -		-105	-95	dBc		
Harmonic Suppression:						
2nd Harmonic		-30	-20	dBc	X	
3rd Harmonic		-44	-25	dBc	X	
Ref Osc Signal:						
Frequency		52		MHz		

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza Microdevices' products are subject to change without notice. Buyers should consult Sirenza Microdevices' standard terms and conditions of sale for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.



Model: PLL250-941

9/1/2006

Rev: P4

Parameter	Min	Typ	Max	Units	X	Remarks
Amplitude	0.75	1	1.25	Vp-p		
Input Impedance		100		k Ω		
Output Impedance -		50		Ω		
Output VSWR -		1.7:1				

Package Information

Package Type:	PLL250 (1 x 1 x 0.252 inches)	Drawing Number:	61070
---------------	-------------------------------	-----------------	-------

Comments

X Indicates parameter to be tested 100% in production

Switching Phase Error: By Design: < 50 us, 2 deg. typical - 5 deg. max.; > 50 us, 1 deg. max

Max Phase Noise Peaking = 5 dBc/Hz, By Design

All Power Supplies decoupled with LCL-Low-Pass filter

All programming lines decoupled with RCR Low-Pass filter

Pin 19 decoupled with RCR Low-Pass filter

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza Microdevices' products are subject to change without notice. Buyers should consult Sirenza Microdevices' standard terms and conditions of sale for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.