

# GPTP1270

## PHASE CONTROLLED SCR

High reliability operation  
Electroplating applications  
Resistance welding applications

**BLOCKING VOLTAGE UP TO**                    **800 V**  
**AVERAGE CURRENT**                        **2700 A**  
**SURGE CURRENT**                            **32 kA**

### BLOCKING CHARACTERISTICS

| Characteristic | Conditions                              | Value                                     |
|----------------|---|---|
| VRRM           | Repetitive peak reverse voltage         | 800 V                                     |
| VRSM           | Non-repetitive peak reverse voltage     | 900 V                                     |
| VDRM           | Repetitive peak off-state voltage       | 800 V                                     |
| IDRM           | Repetitive peak off-state current, max. | VDRM, single phase, half wave, Tj = Tjmax |
| IRRM           | Repetitive peak reverse current, max.   | VRRM, single phase, half wave, Tj = Tjmax |

### ON-STATE CHARACTERISTICS

|                  |  |  |                        |
|------------------|--|--|------------------------|
| IT(AV)           | Average on-state current                 | Sine wave, 180° conduction, Th = 55 °C               | 2700 A                 |
| IT(RMS)          | R.M.S. on-state current                  | Sine wave, 180° conduction, Th = 55 °C               | 4241 A                 |
| ITSM             | Surge on-state current                   | Non rep. half sine wave, 50 Hz, VR = 0 V, Tj = Tjmax | 32 kA                  |
| I <sup>2</sup> t | I <sup>2</sup> t for fusing coordination |  | 5120 kA <sup>2</sup> s |
| VT(TO)           | Threshold voltage                        | Tj = Tjmax   | 0,85 V                 |
| rT               | On-state slope resistance                | Tj = Tjmax   | 0,122 mΩ               |
| VTM              | Peak on-state voltage, max               | On-state current It = 2000 A , Tj = 25 °C            | 1,15 V                 |
| IH               | Holding current, max                     | Tj = 25 °C   | 300 mA                 |
| IL               | Latching current, typ                    | Tj = 25 °C   | 700 mA                 |

### TRIGGERING CHARACTERISTICS

|        |                                |                           |        |
|--------|--------------------------------|---------------------------|--------|
| VGT    | Gate trigger voltage           | Tj = 25 °C, VD = 5 V      | 2,5 V  |
| IGT    | Gate trigger current           | Tj = 25 °C, VD = 5 V      | 300 mA |
| VGD    | Non-trigger voltage            | VD = 67% VRRM, Tj = Tjmax | 0,25 V |
| PGM    | Peak gate power dissipation    | Pulse width 100 μs        | 150 W  |
| PG(AV) | Average gate power dissipation |                           | 2 W    |
| IFGM   | Peak gate current              |                           | 10 A   |
| VFGM   | Peak gate voltage (forward)    |                           | 10 V   |
| VRGM   | Peak gate voltage (reverse)    |                           | 12 V   |


### SWITCHING CHARACTERISTICS

|       |  |  |          |
|-------|--|--|----------|
| di/dt | Critical rate of rise of on-state current  | Tj = Tjmax   | 200 A/μs |
| dV/dt | Critical rate of rise of off-state voltage | Tj = Tjmax   | 500 V/μs |
| tq    | Turn-off time, typ                         | Tj = Tjmax, It = 1000 A, di/dt = -20 A/μs<br>VR = 50 V, VD = 67% VDRM, dV/dt = 20 V/μs | μs       |


### THERMAL AND MECHANICAL CHARACTERISTICS

|          |                                       |                    |              |
|----------|---------------------------------------|--------------------|--------------|
| Rth(j-c) | Thermal resistance (junction to case) | Double side cooled | 0,015 °C/W   |
| Rth(c-h) | Thermal resistance (case to heatsink) | Double side cooled | 0,006 °C/W   |
| Tjmax    | Max operating junction temperature    |                    | 150 °C       |
| Tstg     | Storage temperature                   |                    | -40 / 150 °C |
| F        | Clamping force ± 5%                   |                    | 23 kN        |
|          | Mass                                  |                    | 500 g        |


Current rating - sine wave




Power loss - sine wave





Maximum surge current  
d.s. cooled



On-state voltage drop



Thermal impedance (j-c)



In the interest of product improvement Green Power Solutions reserves the right to change any specification given in this data sheet without notice.