

**isc Silicon NPN Power Transistor**

**MJH16008**

**DESCRIPTION**

- Collector-Emitter Sustaining Voltage-  
:  $V_{CEO(SUS)} = 450V(\text{Min})$
- High Switching Speed

**APPLICATIONS**



- Designed for high-voltage ,high-speed, power switching in inductive circuits where fall time is critical. They are particularly suited for line operated switch-mode applications.  
Typical applications:
- Switching regulators
- Inverters
- Solenoid and relay drivers
- Motor controls
- Deflection circuits

**ABSOLUTE MAXIMUM RATINGS( $T_a=25^\circ\text{C}$ )**

SYMBOL	PARAMETER	VALUE	UNIT
$V_{CEV}$	Collector-Emitter Voltage	850	V
$V_{CEO(SUS)}$	Collector-Emitter Voltage	450	V
$V_{EBO}$	Emitter-Base Voltage	6	V
$I_C$	Collector Current-Continuous	8	A
$I_{CM}$	Collector Current-Peak	16	A
$I_B$	Base Current-Continuous	6	A
$I_{BM}$	Base Current-Peak	12	A
$P_C$	Collector Power Dissipation @ $T_C=25^\circ\text{C}$	125	W
$T_J$	Junction Temperature	150	$^\circ\text{C}$
$T_{stg}$	Storage Temperature	-65~150	$^\circ\text{C}$

**THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	1.0	$^\circ\text{C/W}$



DIM	mm	
	MIN	MAX
A	19.90	20.10
B	15.50	15.70
C	4.70	4.90
D	0.90	1.10
E	1.90	2.10
F	3.40	3.60
G	2.90	3.10
H	3.20	3.40
J	0.595	0.605
K	20.50	20.70
L	1.90	2.10
N	10.89	10.91
Q	4.90	5.10
R	3.35	3.45
S	1.995	2.005
U	5.90	6.10
Y	9.90	10.10

## isc Silicon NPN Power Transistor

## MJH16008

## ELECTRICAL CHARACTERISTICS

 $T_C=25^{\circ}\text{C}$  unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT
$V_{CEO(SUS)}$	Collector-Emitter Sustaining Voltage	$I_C=100\text{mA}$ ; $I_B=0$	450			V
$V_{CE(sat)-1}$	Collector-Emitter Saturation Voltage	$I_C=3\text{A}$ ; $I_B=0.3\text{A}$			2.5	V
$V_{CE(sat)-2}$	Collector-Emitter Saturation Voltage	$I_C=5\text{A}$ ; $I_B=0.5\text{A}$ $I_C=5\text{A}$ ; $I_B=0.5\text{A}$ , $T_C=100^{\circ}\text{C}$			3.0 3.0	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C=5\text{A}$ ; $I_B=0.5\text{A}$ $I_C=5\text{A}$ ; $I_B=0.5\text{A}$ , $T_C=100^{\circ}\text{C}$			1.5 1.5	V
$I_{CEV}$	Collector Cutoff Current	$V_{CEV}=850\text{V}$ ; $V_{BE(off)}=1.5\text{V}$ $V_{CEV}=850\text{V}$ ; $V_{BE(off)}=1.5\text{V}$ ; $T_C=100^{\circ}\text{C}$			0.25 1.5	mA
$I_{CER}$	Collector Cutoff Current	$V_{CE}=850\text{V}$ ; $R_{BE}=50\Omega$ ; $T_C=100^{\circ}\text{C}$			2.5	mA
$I_{EBO}$	Emitter Cutoff Current	$V_{EB}=6\text{V}$ ; $I_C=0$			1.0	mA
$h_{FE}$	DC Current Gain	$I_C=8\text{A}$ ; $V_{CE}=5\text{V}$	7			
$C_{OB}$	Output Capacitance	$I_E=0$ ; $V_{CB}=10\text{V}$ ; $f_{test}=1.0\text{kHz}$			350	pF

Switching times;Resistive Load

$t_d$	Delay Time	$I_C=5\text{A}$ , $V_{CC}=250\text{V}$ ; $R_{B2}=4\Omega$ ; $I_{B1}=0.5\text{A}$ ; $I_{B2}=-1\text{A}$ ; $PW=30\mu\text{s}$ ; Duty Cycle $\leq 2.0\%$		20	50	ns
$t_r$	Rise Time			100	250	ns
$t_s$	Storage Time			900	2200	ns
$t_f$	Fall Time			70	250	ns