Unit: mm

TOSHIBA Photocoupler GaAlAs IRED + Photo IC

TLP350F

Industrial Inverter
Inverter for Air Conditioner
IGBT/Power MOSFET Gate Drive
IH(Induction Heating)

The TOSHIBA TLP350F consists of a GaAlAs light-emitting diode and an integrated photodetector.

This unit is an 8-lead DIP package.

The TLP350F is suitable for gate driving IGBTs or power MOSFETs. Absolute maximum ratings and electrical characteristics are the same as TLP350technical datasheet.

- Peak output current: $I_0 = \pm 2.5 A \text{ (max)}$
- Guaranteed performance over temperature: -40 to 100°C
- Supply current:I_{CC} = 2 mA (max)
- Power supply voltage: Vcc = 15 to 30 V
- Threshold input current : IFLH = 5 mA (max)
- Switching time (t_{pLH}/t_{pHL}): 500 ns (max)
- Common mode transient immunity: 15 kV/us
- Isolation voltage: 3750 Vrms
- UL Recognized: UL1577, File No. E67349
- Option(D4)

VDE Approved: DIN EN 60747-5-2

 $\begin{aligned} & \text{Maximum Operating Insulation Voltage} : 1140 V_{PK} \\ & \text{Highest Permissible Over Voltage} & : 6000 V_{PK} \end{aligned}$

(Note): When an EN60747-5-2 approved type is needed, Please designate "Option(D4)"


• Construction mechanical rating

_	7.62mm pitch TLP350 type	10.16mm pitch TLP350F type
Creepage distance	6.4 mm (min)	8.0 mm (min)
Clearance	6.4 mm (min)	8.0 mm (min)
Insulation thickness	0.4 mm (min)	0.4 mm (min)

8 7 6 5 1 2 3 4 9.66 ± 0.25 90 80 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.25 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25 10.16 ± 0.25


Weight: 0.54 g (typ.)

Pin Configuration (top view)



Truth Table

Input	LED	Tr1	Tr2	Output
Н	ON	ON	OFF	Н
L	OFF	OFF	ON	L



A 0.1 μF bypass capacitor must be connected between pins 8 and 5. (See Note 6)

RESTRICTIONS ON PRODUCT USE

20070701-EN

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
 In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in his document shall be made at the customer's own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No
 responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which
 may result from its use. No license is granted by implication or otherwise under any patents or other rights of
 TOSHIBA or the third parties.
- GaAs(Gallium Arsenide) is used in this product. The dust or vapor is harmful to the human body. Do not break, cut, crush or dissolve chemically.
- Please contact your sales representative for product-by-product details in this document regarding RoHS
 compatibility. Please use these products in this document in compliance with all applicable laws and regulations
 that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses
 occurring as a result of noncompliance with applicable laws and regulations.