


BTA06**◆ Features**

- With TO-220AB Insulated package
- Suitable for general purpose applications where gate high sensitivity is required ,such as phase control and static switching applications

**◆ QUICK REFERENCE DATA**

SYMBOL	PARAMETER	VALUE	UNIT			
V_{DRM}	Repetitive peak off-state voltage	600	V			
V_{RRM}	Repetitive peak off-state voltage	600	V			
$I_{T(AV)}$	Average on-state current	6	A			
I_{TSM}	Non-repetitive peak on-state current	60	A			
T_{stg}	Storage temperature	-45 ~ 150				
T_j	Operating junction temperature	110				TO-220AB

◆ ELECTRICAL CHARACTERISTICS ($T_j = 25^\circ\text{C}$, unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V_{DRM}	Repetitive peak off-state voltage	$I_D=0.1\text{mA}$	600		V
V_{RRM}	Repetitive peak reverse voltage	$I_D=0.5\text{mA}$	600		V
I_{GT}	Gate trigger current	$V_D=12\text{V}; R_L = 100 \Omega; T2+ G+$		25	mA
		$T2+ G-$		35	
		$T2- G-$		35	
		$T2- G+$...	
V_T	On-state voltage	$I_T=8.5\text{A}$		1.65	V
I_H	Holding current	$I_T=0.1\text{A}; I_{GT} = 50\text{mA}$		50	mA
V_{GT}	Gate trigger voltage	$V_D=12\text{V}; R_L = 100 \Omega; T2+ G+$		1.5	V
		$T2+ G-$		1.5	
		$T2- G-$		1.5	
		$T2- G+$		1.8	