

DIELECTRIC RESONATOR OSCILLATOR

MDR2100-14500

14500 - 15500 MHz

Features


- Rugged Construction for Extreme Environmental Conditions
- High Frequency Stability
- Free Running, Mechanically Tuned

Specifications¹

CHARACTERISTIC	TYPICAL Ta = +25 °C	MIN/MAX Ta = -20°C to +65 °C	
Frequency	14500 - 15500 MHz	14500 - 15500 MHz	
Mechanical Tuning Bandwidth (MHz)	—	±20 Min.	
Frequency Stability ² (ppm)/ °C	4	5 Max.	
Pulling, 12 dB RL (ppm)	—	±100 Max.	
Pushing (ppm/Volt)	—	20 Max.	
Harmonics (dBc)	-20	-15 Max.	
Spurious (dBc)	-75	-70 Max.	
Output Power (dBm) ³	+11	+10 Min.	
Power	Vdc ⁴ mA	+15 120	+15 125 Max.

NOTES: Care should always be taken to effectively ground the case of each unit.

1. Specifications labeled "min." or "max." are guaranteed in a 50 Ohm system over the specified temperature range.
2. Averaged over the full temperature range.
3. Higher output power is available.
4. Alternate input voltage is available.
5. Package must be verified by Spectrum Microwave.



Absolute Maximum Ratings

Ambient Operating Temperature -55°C to +100 °C
 Storage Temperature -62°C to +125 °C
 Case Temperature +125 °C
 DC Voltage +24 Volts

Typical Performance Data

Phase Noise	Typical 14500 MHz	Typical 15500 MHz
Offset		
10 kHz	-92	-92
100 kHz	-117	-117
1 MHz	-137	-137

Phase Noise (dBc/Hz)
14500 MHz

