


MOS Field Effect Transistor

2SK3794

■ Features

- Low On-state resistance
 $R_{DS(on)1} = 44 \text{ m}\Omega \text{ MAX. } (V_{GS} = 10 \text{ V}, I_D = 10 \text{ A})$
 $R_{DS(on)2} = 78 \text{ m}\Omega \text{ MAX. } (V_{GS} = 4.0 \text{ V}, I_D = 10 \text{ A})$
- Low C_{iss} : $C_{iss} = 760 \text{ pF TYP.}$
- Built-in gate protection diode



■ Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Rating | Unit |
|---|------------|-------------|------------------|
| Drain to source voltage | V_{DSS} | 60 | V |
| Gate to source voltage | V_{GSS} | ± 20 | V |
| Drain current | I_D | ± 20 | A |
| | I_{Dp}^* | ± 50 | A |
| Power dissipation $T_A=25^\circ\text{C}$ $T_C=25^\circ\text{C}$ | P_D | 1.5 | W |
| | | 30 | |
| Channel temperature | T_{ch} | 150 | $^\circ\text{C}$ |
| Storage temperature | T_{stg} | -55 to +150 | $^\circ\text{C}$ |

* $PW \leq 10 \mu\text{s}$, Duty Cycle $\leq 1\%$

■ Electrical Characteristics $T_a = 25^\circ\text{C}$

| Parameter | Symbol | Testconditons | Min | Typ | Max | Unit |
|-------------------------------------|---------------|---|-----|-----|----------|------------------|
| Drain cut-off current | I_{DSS} | $V_{DS}=60\text{V}, V_{GS}=0$ | | | 10 | μA |
| Gate leakage current | I_{GSS} | $V_{GS}=\pm 20\text{V}, V_{DS}=0$ | | | ± 10 | μA |
| Gate cut off voltage | $V_{GS(off)}$ | $V_{DS}=10\text{V}, I_D=1\text{mA}$ | 2.5 | 3.5 | 4.5 | V |
| Forward transfer admittance | $ Y_{fs} $ | $V_{DS}=10\text{V}, I_D=10\text{A}$ | 7.0 | 15 | | S |
| Drain to source on-state resistance | $R_{DS(on)1}$ | $V_{GS}=10\text{V}, I_D=10\text{A}$ | | 35 | 44 | $\text{m}\Omega$ |
| | $R_{DS(on)2}$ | $V_{GS}=4.0\text{V}, I_D=10\text{A}$ | | 54 | 78 | $\text{m}\Omega$ |
| Input capacitance | C_{iss} | $V_{DS}=10\text{V}, V_{GS}=0, f=1\text{MHZ}$ | | 760 | | pF |
| Output capacitance | C_{oss} | | | 150 | | pF |
| Reverse transfer capacitance | C_{rss} | | | 71 | | pF |
| Turn-on delay time | t_{on} | | | 13 | | ns |
| Rise time | t_r | $I_D=10\text{A}, V_{GS(on)}=10\text{V}, R_G=0\Omega, V_{DD}=30\text{V}$ | | 170 | | ns |
| Turn-off delay time | t_{off} | | | 43 | | ns |
| Fall time | t_f | | | 34 | | ns |
| Total Gate Charge | Q_G | | | 17 | | nC |
| Gate to Source Charge | Q_{GS} | $V_{DD} = 48\text{V}$ $V_{GS} = 10 \text{ V}$ $I_D = 10\text{A}$ | | 3.0 | | nC |
| Gate to Drain Charge | Q_{GD} | | | 4.7 | | nC |