



**Sparkle Power Inc.**  
 A Leading Power Supply Manufacturer  
 Web site: [www.sparklepower.com](http://www.sparklepower.com)



## ATX-400PN

### 400 Watts ATX12V 2.01 Switching Power Supply

#### Features

- Complied with ATX12V 2.0 standard
- High efficiency and reliability
- Remote On/Off function
- Internal 12V DC fan included
- Noise Killer (Thermal fan speed control function)
- Low noise and ripple
- Complies with FCC part 15 subpart J Class B and CISPR 22 Class B
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Approved by UL 60950, IEC 60950, TUV EN60950, NEMKO (CB Report)

#### Input Characteristics

**Input Range:** 100~132Vrms or 200~264Vrms, Manual selection

**Frequency:** 47~63Hz

**Input Current:** 8.5A (RMS) @115Vrms/60Hz, 5A (RMS) @ 230Vrms/50Hz

**Inrush Current:** 100A Max cold start, 120A Max warm start measured at 264Vrms/50Hz

#### Output Characteristics

Output Voltage	Minimum Load	Normal Load	Maximum Load	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.5A	15.0A	30A	± 5%	± 1%	50mV P-P
+5V	1.0A	14.0A	28A	± 5%	± 1%	50mV P-P
+12V1DC	1.0A	7.0A	18A	± 5%	± 1%	120mV P-P
+12V2DC	1.0A	8.5A	18A	± 5%	± 1%	120mV P-P
-12V	0.0A	0.4A	0.5A	± 10%	± 2%	120mV P-P
+5Vsb	0.0A	1.0A	2.0 A	± 5%	± 1%	50mV P-P

\*+3.3V and +5V total output not exceed 150W

When +3.3V is load to 30A, the +5V maximum load is 10A

When +3.3V is load to 3.0A, the +5V maximum load is 28A

\*+12V1DC, 12V2DC total power not exceed 348W

\*+3.3V, +5V, +12V1DC, and +12V2DC total output not exceed 385W

#### Specification

- **Temperature Range:** Operating 0° C ~ +25° C on full load; De-rate 2W/°C from +25°C to +50°C. Storage & shipping -20° C ~ +65° C
- **Humidity:** 90% on operating and 95% on storage
- **Dielectric Withstand:** Input to frame ground 1800V AC for 1 second
- **Efficiency: 70%** minimum measured at nominal AC main voltage and frequency with maximum loads on all outputs
- **Rise Time:** Less than 20ms on all outputs
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Not exceed 3.5mA
- **MTBF:** 100,000 hours on maximum load at +25° C
- **Dimension (WxHxL):** 150x86x140mm / 6x3.4x5.5inches

**Sparkle Power Inc.**  
**Main Office**  
 1000 Rock Avenue  
 San Jose, CA 95131  
 TEL: 408-519-8888  
 FAX: 408-519-9999  
 E-MAIL: [info@sparklepower.com](mailto:info@sparklepower.com)

**Sparkle Power Inc.**  
**Los Angeles Office**  
 17071 Green Drive  
 City of Industry, CA 91745  
 TEL: 626-839-7180  
 FAX: 626-839-3395

**Sparkle Power Inc.**  
**Colorado Office**  
 1316 Indian Paintbrush Lane  
 Longmont, CO 80503  
 TEL: 303-776-3281  
 FAX: 303-776-7645