

Silicon PNP Power Transistors

BDV64/64A/64B/64C

DESCRIPTION

- With TO-3PN package
- Complement to type BDV65/65A/65B/65C
- DARLINGTON
- High DC current gain

APPLICATIONS

- For use in general purpose amplifier applications.

PINNING

PIN	DESCRIPTION
1	Base
2	Collector;connected to mounting base
3	Emitter




Fig.1 simplified outline (TO-3PN) and symbol

Absolute maximum ratings(Tc=25)

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT	
V _{CBO}	Collector-base voltage	Open emitter	BDV64	-60	V
			BDV64A	-80	
			BDV64B	-100	
			BDV64C	-120	
V _{CEO}	Collector-emitter voltage	Open base	BDV64	-60	V
			BDV64A	-80	
			BDV64B	-100	
			BDV64C	-120	
V _{EBO}	Emitter-base voltage	Open collector	-5	V	
I _C	Collector current		-12	A	
I _{CM}	Collector current-peak		-15	A	
I _B	Base current		-0.5	A	
P _C	Collector power dissipation	T _C =25	125	W	
		T _a =25	3.5		
T _j	Junction temperature		150		
T _{stg}	Storage temperature		-65~150		

Silicon PNP Power Transistors

BDV64/64A/64B/64C

CHARACTERISTICS

T_j=25 unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP.	MAX	UNIT	
V _{(BR)CEO}	Collector-emitter breakdown voltage	BDV64	-60			V	
		BDV64A	-80				
		BDV64B	-100				
		BDV64C	-120				
V _{CEsat}	Collector-emitter saturation voltage	I _C =-5A, I _B =-20mA			-2.0	V	
V _{BE}	Base-emitter on voltage	I _C =-5A; V _{CE} =-4V			-2.5	V	
I _{CBO}	Collector cut-off current	BDV64	V _{CB} =-60V, I _E =0 V _{CB} =-30V, I _E =0; T _C =150			-0.4 -2.0	mA
		BDV64A	V _{CB} =-80V, I _E =0 V _{CB} =-40V, I _E =0; T _C =150			-0.4 -2.0	
		BDV64B	V _{CB} =-100V, I _E =0 V _{CB} =-50V, I _E =0; T _C =150			-0.4 -2.0	
		BDV64C	V _{CB} =-120V, I _E =0 V _{CB} =-60V, I _E =0; T _C =150			-0.4 -2.0	
I _{CEO}	Collector cut-off current	BDV64	V _{CE} =-30V, I _B =0			-2	mA
		BDV64A	V _{CE} =-40V, I _B =0				
		BDV64B	V _{CE} =-50V, I _B =0				
		BDV64C	V _{CE} =-60V, I _B =0				
I _{EBO}	Emitter cut-off current	V _{EB} =-5V; I _C =0			-5	mA	
h _{FE}	DC current gain	I _C =-5A; V _{CE} =-4V	1000				
V _{EC}	Diode forward voltage	I _E =-10A			-3.5	V	

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
R _{th j-c}	Thermal resistance junction to case	1.0	/W

Silicon PNP Power Transistors

BDV64/64A/64B/64C

PACKAGE OUTLINE

