

## EPC3094-X


- Single Primary : 115 V
- Split Bobbin Construction
- UL 94V-0 Recognized Components
- UL 1446 Class B Insulation System
- Meets or exceeds CSA/TUV/VDE Specifications for Creepage, Clearance and Dielectric Strength

### Electrical Parameters @ 25° C


Part Number	Primary Voltage	Secondary Voltage		Secondary Current (A-Rms)		Power Rating (VA)
		Parallel Connection	Series Connection	Parallel Connection	Series Connection	
EPC3094-1	115	5.0	10	7.20	3.60	36
EPC3094-2	115	6.3	12.6	5.70	2.85	36
EPC3094-3	115	8.0	16	4.50	2.25	36
EPC3094-4	115	10	20	3.60	1.80	36
EPC3094-5	115	12	24	3.00	1.50	36
EPC3094-6	115	14	28	2.60	1.30	36
EPC3094-7	115	18	36	2.00	1.00	36
EPC3094-8	115	24	48	1.50	0.75	36
EPC3094-9	115	28	56	1.30	0.65	36
EPC3094-10	115	60	120	0.60	0.30	36

• Switching Frequency : 50 Hz - 500 Hz • Isolation : 2500 Vrms •

### Package



### Schematic



### Notes :

1. Optional Mounting Screws and Nut : Size #6 Screw
2. Pins 2 and 3 omitted

Unless Otherwise Specified Dimensions are in Inches /mm ±.010 / .25