


SUPER FAST GLASS PASSIVATED RECTIFIERS	REVERSE VOLTAGE - 50 to 600 Volts FORWARD CURRENT - 3.0 Amperes
---	--

FEATURES

- Super fast switching time for high efficiency
- Low forward voltage drop and high current capability
- Low reverse leakage current
- Plastic material has UL flammability classification 94V-0

MECHANICAL DATA

- Case: JEDEC DO-27 molded plastic
- Polarity: Color band denotes cathode
- Weight: 0.04 ounces , 1.1 grams
- Mounting position: Any



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Rating at 25°C ambient temperature unless otherwise specified.
 Single phase, half wave ,60Hz, resistive or inductive load.
 For capacitive load, derate current by 20%

CHARACTERISTICS	SYMBOL	SF31G	SF32G	SF33G	SF34G	SF35G	SF36G	SF38G	UNIT	
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	150	200	300	400	600	V	
Maximum RMS Voltage	VRMS	35	70	105	140	210	280	420	V	
Maximum DC Blocking Voltage	VDC	50	100	150	200	300	400	600	V	
Maximum Average Forward Rectified Current @TA =55 °C	I(AV)	3.0							A	
Peak Forward Surge Current 8.3ms Single Half Sine-Wave Super Imposed on Rated Load(JEDEC Method)	IFSM	125							A	
Peak Forward Voltage at 3.0A DC	VF	0.95			1.25		1.3		V	
Maximum DC Reverse Current at Rated DC Blocking Voltage @TJ=25°C @TJ=100°C	IR	5.0				100				µA
Maximum Reverse Recovery Time(Note 1)	Trr	35			40		50		nS	
Typical Junction Capacitance (Note2)	CJ	70			45				pF	
Typical Thermal Resistance (Note3)	RθJA	20							°C/W	
Operating Temperature Range	TJ	-55 to +125							°C	
Storage Temperature Range	TSTG	-55 to +150							°C	

NOTES: 1. Measured with IF=0.5A, IR=1A, IRR=0.25A.
 2. Measured at 1.0 MHz and applied reverse voltage of 4.0V DC
 3. Thermal resistance junction to ambient,

FIG. 1 – FORWARD CURRENT DERATING CURVE




FIG. 2 – MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 – TYPICAL JUNCTION CAPACITANCE




FIG.4-TYPICAL FORWARD CHARACTERISTICS

