FEATURES

- · 0...1 bar gage pressure
- · For corrosive pressure media
- · Low temperature drift
- All welded stainless steel diaphragm construction
- · Really flat diaphragm
- · For hostile environments

SERVICE

Media wetted parts: any liquid or vapor that is compatible with stainless steel 316L (1.4401)



Scale:	1 cm
μ <u> </u>	1 inch

ELECTRICAL CONNECTION

SPECIFICATIONS

Maximum ratings

Supply voltage	6 V
Temperature limits Storage Operating Compensated	-40°C to 70°C -40°C to 70°C 10°C to 40°C
Vibration (5 Hz to 500 Hz)	2 g _{RMS}
Mechanical shock (11 ms)	50 g
Proof pressure ¹	3 bar



March 2001 / 081

SENSOR IECHNICS

SSC1001GA

Temperature compensated silicon stainless steel pressure sensors

PERFORMANCE CHARACTERISTICS

(unless otherwise noted, $V_s = 5 \text{ V}$, $t_{amb} = 25^{\circ}\text{C}$)

Characteristics	Min.	Тур.	Max.	Unit
Operating pressure			1	bar
Zero pressure offset	-0.75		0.75	m)/
Full scale span ²	13.7	14.5	15.3	IIIV
Combined non-linearity ³ , hysteresis and temperature variation, $t_{amb} = 10$ to 40° C		±1.0	±4.0	%FSO
Maximum current consumption		5.0		mA
Output impedance		350		Ω
Common mode voltage		2.5		V
Response time		100		μs
Life time		50000		hours

Specification notes (for all devices):

- 1. Proof pressure is the max. pressure which may be applied without causing damage to the sensing element.
- 2. Span is the algebraic difference between the output at full scale pressure and offset.
- 3. Non-linearity the maximum deviation of measured output at constant temperature, from "Best Straight Line" through three points (offset pressure, full scale pressure and half scale pressure).



OUTLINE DRAWING

mass: 7 g

2/2

Sensortechnics reserves the right to make changes to any products herein. Sensortechnics does not assume any liability arising out of the application or use of any product or circuit described herein, neither does it convey any license under its patent rights nor the rights of others.

March 2001 / 081

SENSOR IECHNICS

www.sensortechnics.com