



ESD protection and signal booster for HDMI™ 1.3 Tx control links

Data Brief

Features

- HDMI 1.3. compliant from -40 to 85 °C
- CEC, DDC, 5 V and HPD 8 kV contact ESD protection
- Integrated I²C bi-directional reshaping circuit and level-shifter
- Integrated CEC bi-directional level-shifter with dV/dt limiter
- Supports direct connection to low-voltage HDMI ASICs (down to 1.8 V)
- Backdrive current protection on all I/O pins
- HDMI short-circuit and overcurrent protection on 5 V output
- Long HDMI cable drive support
- 500 µm pitch

Benefits

- Most stringent ESD standards compliance guaranteed at system level
- Full protection of ultra-sensitive HDMI ASICs
- Optimized HDMI control signal shapes guaranteed at connector level
- Signal booster for long HDMI cable support
- High integration
- Companion chip for HDMIULC6-xxx6 ultra-large bandwidth ESD protection for TMDS links
- Companion chip for STMicroelectronics' STixxxx HDMI HD decoders.
- Referenced in STi7111-SAT-MB-V1.2-011 reference design from STMicroelectronics

Complies with the following standards:

- IEC61000-4-2 level 4
- JESD22-A114D level 2



Applications

- Consumer and computer electronics
- HD set-top boxes, DVD and flat television sets
- PC graphic cards

Description

The HDMI2C1-5DIJ is a fully integrated ESD protection, level-shifting device and signal booster for control links of HDMI 1.3 transmitters.

This device is a bi-directional isolation buffer, integrating hysteresis and signal boosters for maximum system robustness and signal integrity. All these features are provided in a single 16-lead QFN package featuring straightforward routing.

The HDMI2C1-5DIJ is a simple plug and play device that provides HDMI designers with an easy way to gain full compliance with the stringent HDMI 1.3 CTS on a wide temperature range.

TM: HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC.

1 Ordering information

Table 1. Ordering information

Order code	Marking	Package	Weight	Base qty	Delivery mode
HDMI2C1-5DIJ	HDM1	QFN 5x4 16-lead	60 mg	3000	Tape and reel

2 Revision history

Table 2. Document revision history

Date	Revision	Changes
05-Feb-2009	1	Initial release.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2009 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com