


M9004 Series

LVPECL/LVDS/CMOS Frequency Translator

The MtronPTI Frequency Translator is a miniature, self contained, high performance Phase Locked Loop synthesizer. It is intended for coherent frequency translation with noise reduction. It can be used anywhere accurate frequency synchronization, multiplication and noise and jitter reduction is needed. Based on MtronPTI's unique Qik Chip technology, virtually any input frequency in the range of 8 KHz to 622 MHz can be translated to any frequency in the range of 19.44MHz to 1.4 GHz. The M9004 Series features a loss of lock indicator that can also be used to detect a loss of reference. An enable/disable function is also standard. Outputs at PECL, LVDS and CMOS levels are available.

Ordering Information



Applications include:

- Translation of 155 MHz to 622 or 1244 MHz (Sonet/SDH synchronization)
- Translation of 1.544 MHz to 38.88 or 155.52 MHz. (DS1 to SDH synchronization)
- Custom frequency translation up to 1.4 GHz.
- Jitter reduction.
- Phase noise improvement
- Frequency distribution applications.


	Parameter	Min.	Typ.	Max.	Units	Conditions/Notes	
Electrical Specifications	Input Frequency Range	.008		622	MHz		
	Output Frequency Range	19.44		1400	MHz	LVPECL/LVDS	
		19.44		200	MHz	CMOS	
	Supply Voltage	3.3 Volt (±5%)					
	Input Level (dBm 50 Ohms)	-3		+7	dBm		
	PECL Output	Logic "0" Vcc-1.63 V Logic "1" Vcc-1.02 V					
	Current Drain		135		mA		
	Operating Temperature	-40°C to +85°C					
	Input Frequency Tracking Capability	±50			ppm		
	Jitter Attenuation	3 dB @ 100 Hz offset 30 dB @ 1kHz offset					Loop characteristics can be adjusted to match customer requirements
RMS Phase Jitter Generation		<0.45	<1	psec	10 kHz to 20 MHz		
Spurious Output Levels	Reference sidebands <-40 dBc All other spurious <-60 dBc						
Environmental	Storage Temperature	-40°C to +90°C					
	Humidity	95%, relative humidity max @ 70°C					
	Vibration	10 to 60 Hz with double amplitude of 1.52mm max.					(1/2 hour in each of 3 perpendicular planes)
	Shock	½ sine pulse, 3000G, with pulse width 0.3 mSec					(3 shock in each of 6 directions of 3 perpendicular planes)
	Maximum Soldering Profile	See +260°C Reflow Profile					

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.


M9004 Series

LVPECL/LVDS/CMOS Frequency Translator




PAD 1: Lock Detect	PAD 6: Complementary \bar{Q}
PAD 2: Input Frequency	PAD 7: Output Q
PAD 3: Complementary Input	PAD 8: +Vcc Power Supply
PAD 4: Ground	PAD 9: N/C
PAD 5: Enable/Disable	PAD 10: Ground

Wiring Diagram



Circuit Diagram




MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.


Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

Typical Phase Noise

155 MHz to 622 MHz Frequency Translator



Lead Free Solder Profile



MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.