



===== CONTENTS =====

1. GENERAL DESCRIPTION	3
2. FEATURES	3
3. BLOCK DIAGRAM	3
4. PIN ASSIGNMENT	4
5. ELECTRICAL CHARACTERISTICS	4
5.1. ABSOLUTE MAXIMUM RATINGS	4
5.2. DC CHARACTERISTICS (TA=25°C).....	5
6. APPLICATION CIRCUIT	6
6.1. CURRENT DAC APPLICATION WITH SINGLE-END MODE	6
6.2. PWM WITH DIFFERENTIAL MODE	7
6.3. PUSH-PULL DAC WITH SINGLE-END MODE	8
6.4. PUSH-PULL DAC WITH DIFFERENTIAL MODE.....	9
6.5. SINGLE-END WITH MIXED	10
6.6. DIFFERENTIAL MODE WITH MIXED	11
7. PACKAGE/PAD LOCATIONS	12
7.1. SNAP01H (DICE)	12
7.2. SNAP01PG (DIP GREEN PACKAGE).....	13
7.3. SNAP01SG (SOP GREEN PACKAGE).....	14



AMENDMENT HISTORY

VERSION	DATE	DESCRIPTION
V1.0	September 27, 2007	First issue
V1.1	October 9, 2007	Advise Application Circuit
V1.2	November 2, 2007	Revise Package information.
V1.3	November 22, 2007	1. Revise Operation current. 2. Revise package information.


1. General Description

The SNAP01 is an integrated class AB mono speaker driver. The SNAP01 consist of single power supply, no switch-on/off click, high SNR ratio, power control, single-end/differential input mode and support Gain adjusted by external resistor.


2. Features

- w Operation voltage : 2.4V-5.5V.
- w High signal-to-noise ratio.
- w Low distortion.
- w High slew rate.
- w No switch On/Off click.
- w Power off control.
- w Gain adjustment.
- w Large output voltage swing.
- w Direct driver speaker.
- w Support single-end and differential mode.
- w Low standby current : 1.0 μ A.

3. Block Diagram



4. Pin Assignment



Pin No.	Symbol	I/O	Function Description
1	VM	I	Signal Input Positive
2	VIN	I	Signal Input Negative
3	GND	I	Negative Power Supply
4	VREF	O	Voltage Reference
5	CE	I	Chip Enable, High Active
6	O+	O	Positive Output
7	VDD	I	Positive Power Supply
8	O-	O	Negative Output

5. Electrical Characteristics


5.1. Absolute Maximum Ratings

Characteristic	Symbol	Min	Max	Unit
Supply Voltage	VDD	-0.3	6.0	V
Operating Temperature	T _{OG}	0	55	°C
Storage Temperature	T _{STG}	-55	125	°C

5.2. DC Characteristics (Ta=25°C)


Parameter	Symbol	Min	Typical	Max	Unit	Condition
Supply Power	V _{DD}	2.4	-	5.5	V	
Standby Current	I _{STB}	-	-	1	μA	CE=Low
Operating Current	I _{OP}	-	-	12	mA	V _{DD} =3.0V, CE=High, No load & V _{IN} and V _M is floating.
		-	-	16	mA	V _{DD} =4.5V CE=High, No load & V _{IN} and V _M is floating.
Chip Enable	CE		V _{DD} /3		V	V _{CE} >2/3V _{DD} = High V _{CE} <1/3V _{DD} = Low
Reference Voltage	V _{REF}	-	V _{DD} /2	-	V	CE=High, CE=Low, V _{REF} =V _{DD}
Output Current	I _o	-	180	-	mA	V _{DD} =3.0V, R _L =8Ω
		-	360	-	mA	V _{DD} =4.5V, R _L =8Ω
Signal to Noise Ratio	SNR	-	57	-	dB	Single-End Mode
		-	72	-	dB	Differential Mode
The Harmonic Distortion + Noise	THD+N	-	-	1	%	V _{DD} =3.0V, R _L =8Ω P=0.25W
		-	-	1	%	V _{DD} =4.5V, R _L =8Ω P=0.58W
Output Power	P _{OUT}	0.5	0.58	-	W	V _{DD} =4.5V, R _L =8Ω, THD+N=1%
		0.7	0.75	-	W	V _{DD} =4.5V, R _L =8Ω, THD+N=10%
Enable Time	T _{ON}	-	16	-	ms	V _{DD} =4.5V
		-	32	-	ms	V _{DD} =3.0V
Gain			15			Single-end mode Gain=75K/(5K+R1)
			30			Differential-mode Gain=75K/(5K+R1)

Note1 : T_{ON} is the time from CE high (chip enable) to O+ or O- output.




6. Application Circuit


6.1. Current DAC application with Single-End Mode




6.2. PWM with Differential Mode




6.3. Push-Pull DAC with Single-End Mode




6.4. Push-Pull DAC with Differential Mode



6.5. SINGLE-END with MIXED



6.6. Differential Mode with Mixed




7. PACKAGE/PAD LOCATIONS

7.1. SNAP01H (Dice)

PAD Assignment

NO	PAD NAME	X(um)	Y(um)	NO	PAD NAME	X(um)	Y(um)
1	VM	-495.31	-370.90	6	O+	375.49	234.14
2	VIN	-385.31	-370.90	7	O+	375.49	349.14
3	GND	-21.41	-295.15	8	VDD	-21.41	291.64
4	VREF	385.31	-370.90	9	O-	-418.31	349.14
5	CE	495.31	-370.90	10	O-	-418.31	234.14



CHIP SIZE: X=1124um,Y=960um


Note: 1.The VDD pin MUST bonding to VDD in PCB layout.

2.The substrate MUST be connected to GND in PCB layout.

7.2. SNAP01PG (DIP Green Package)

8-pin DIP (300mil) Outline Dimensions


Pin No.	Symbol	I/O	Function Description
1	VM	I	Signal Input Positive
2	VIN	I	Signal Input Negative
3	GND	I	Negative Power Supply
4	VREF	O	Voltage Reference
5	CE	I	Chip Enable, High Active
6	O+	O	Positive Output
7	VDD	I	Positive Power Supply
8	O-	O	Negative Output



7.3. SNAP01SG (SOP Green Package)

8-pin SOP (150mil) Outline Dimensions

Pin No.	Symbol	I/O	Function Description
1	VM	I	Signal Input Positive
2	VIN	I	Signal Input Negative
3	GND	I	Negative Power Supply
4	VREF	O	Voltage Reference
5	CE	I	Chip Enable, High Active
6	O+	O	Positive Output
7	VDD	I	Positive Power Supply
8	O-	O	Negative Output



DISCLAIMER

The information appearing in SONiX web pages (“this publication”) is believed to be accurate.

However, this publication could contain technical inaccuracies or typographical errors.

The reader should not assume that this publication is error-free or that it will be suitable for any particular purpose. SONiX makes no warranty, express, statutory implied or by description in this publication or other documents which are referenced by or linked to this publication. In no event shall SONiX be liable for any special, incidental, indirect or consequential damages of any kind, or any damages whatsoever, including, without limitation, those resulting from loss of use, data or profits, whether or not advised of the possibility of damage, and on any theory of liability, arising out of or in connection with the use or performance of this publication or other documents which are referenced by or linked to this publication.

This publication was developed for products offered in Taiwan. SONiX may not offer the products discussed in this document in other countries. Information is subject to change without notice. Please contact SONiX or its local representative for information on offerings available. Integrated circuits sold by SONiX are covered by the warranty and patent indemnification provisions stipulated in the terms of sale only. The application circuits illustrated in this document are for reference purposes only. SONiX DISCLAIMS ALL WARRANTIES, INCLUDING THE WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE. SONiX reserves the right to halt production or alter the specifications and prices, and discontinue marketing the Products listed at any time without notice. Accordingly, the reader is cautioned to verify that the data sheets and other information in this publication are current before placing orders.

Products described herein are intended for use in normal commercial applications. Applications involving unusual environmental or reliability requirements, e.g. military equipment or medical life support equipment, are specifically not recommended without additional processing by SONiX for such application.