

Applications

- DSSS 2.4 GHz WLAN (IEEE802.11b)
- OFDM 2.4 GHz WLAN (IEEE802.11g)
- Access Points, PCMCIA, PC cards

Features

- Single 3.3 V Supply Operation
 - 21 dBm, EVM = 3 %, 802.11g, OFDM 54 Mbps
 - o 24 dBm, ACPR < -32 dBc, 802.11b
- Dual Supply Operation
 - 23 dBm, EVM = 3 %, 802.11g, OFDM 54 Mbps
 - o 25 dBm, ACPR < -32 dBc, 802.11b
- 32 dB Gain
- Pin for pin compatible to the SE2525L
- Integrated temperature compensated power detector
- Integrated power amplifier enable pin (VEN)
- Lead Free and RoHS compliant
- Small package: 16 pin 4 mm x 4 mm x 0.9 mm

Product Description

The SE2527L is a 2.4 GHz power amplifier designed for use in the 2.4 GHz ISM band for wireless LAN applications. The device incorporates a power detector for closed loop monitoring of the output power.

The SE2527L also offers a high power mode by operating at 5 V. This provides an extra 2 dB of improved EVM performance.

The SE2527L includes a digital enable control for device on/off control.

The device is pin for pin compatible to SiGe's SE2524L, allowing both devices to share the same application board with only a few component changes required. This provides users with both a high and low power solution without changing the layout.

The SE2527L temperature compensated power detector is highly immune to mismatch at its output with less than 1.5 dB of variation with a 2:1 mismatch.

Ordering Information

Part Number	Package	Remark
SE2527L	16 Pin QFN	Samples
SE2527L-R	16 Pin QFN	Tape and Reel
SE2527L-AK1	Application Kit	Standard

Functional Block Diagram




Figure 1: Functional Block Diagram



2.4 GHz Power Amplifier with Power Detector Preliminary Information

http://www.sige.com

Email: sales@sige.com

Customer Service Locations:

North America:

 1050 Morrison Drive, Suite 100
 Phone: +852 3428 7222

 Ottawa ON K2H 8K7 Canada
 Fax: +852 3579 5450

Phone: +1 613 820 9244 San Diego

Fax: +1 613 820 4933 Phone: +1 858 668 3541 (ext. 226)

Fax: +1 858 668 3546

United Kingdom

Hong Kong

Phone: +44 1279 464217 Fax: +44 1279 464201

Product Preview

The datasheet contains information from the product concept specification. SiGe Semiconductor, Inc. reserves the right to change information at any time without notification.

Preliminary Information

The datasheet contains information from the design target specification. SiGe Semiconductor, Inc. reserves the right to change information at any time without notification.

Production testing may not include testing of all parameters.

Information furnished is believed to be accurate and reliable and is provided on an "as is" basis. SiGe Semiconductor, Inc. assumes no responsibility or liability for the direct or indirect consequences of use of such information nor for any infringement of patents or other rights of third parties, which may result from its use. No license or indemnity is granted by implication or otherwise under any patent or other intellectual property rights of SiGe Semiconductor, Inc. or third parties. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SiGe Semiconductor, Inc. products are NOT authorized for use in implantation or life support applications or systems without express written approval from SiGe Semiconductor, Inc.

Copyright 2009 SiGe Semiconductor, Inc. All Rights Reserved

