

ISOLATED DC/DC CONVERTERS

48 VDC Input 12 VDC/27 A Output, 1/4 Brick

bel
POWER PRODUCTS

0RCM-27S12L

RoHS Compliant

Rev.A

- Industry standard quarter-brick package
- Up to 300 W at 95% efficiency
- 1500 V isolation
- Safety Agency Approvals



Description

The 0RCM-27S “Cimarron” Series are isolated DC/DC converters that operate from a nominal 48 VDC source. These converters use a full bridge power train to provide isolation and step down. These units will provide up to 300 W of output power from a nominal 48 VDC input. These units are designed to be highly efficient and low cost. Features include remote on/off, over current protection and under voltage lockout. These converters are provided in an industry standard quarter-brick package.

Part Selection

Output Voltage	Input Voltage	Max. Output Current	Max. Output Power	Typical Efficiency	Model Number
12 Vdc	48 Vdc	27 A	300 W	95%	0RCM-27S12L

Notes: 1. Add “G” suffix at the end of the model number to indicate Tray Packaging.

2. All part numbers above indicate RoHS 6. Change the second letter “R” to “7” for RoHS 5 part numbers.

Input Specifications

Parameter	Min	Typ	Max	Notes
Input Voltage Range	36 V	-	55 V	
Input Current (no load)	-	-	110 mA	
Input Current (full load)	-	-	6.82 A	
Reflected Ripple Current (rms)	-	-	50 mA	with a 12uH source inductor at nom. Vin and full load.
Reflected Ripple Current (pk-pk)	-	-	100 mA	
Under-voltage Lockout	Turn-on	-	35.8 V	-
	Turn off	-	33.8 V	-
Over-voltage Lockout	-	57.1 V	-	

ISOLATED DC/DC CONVERTERS

48 VDC Input 12 VDC/27 A Output, 1/4 Brick



Output Specifications

Parameter	Min	Typ	Max	Notes
Output Voltage 36V _{in} 48V _{in} 55V _{in}	- - -	8.7 V 11.7 V 13.3 V	- - -	Setpoint at no load.
Output Current	0 A	-	27 A	
Output Power	-	-	300 W	
Load Regulation	-	-	0.4 V	
Ripple and Noise (pk-pk)	-	-	150 mV	0 to 20 MHz Bandwidth, use 1.0 uF ceramic cap and 100 uF/50mOhm tantalum on output
Load Capacitance	100 uF (50mohm)	-	3000 uF	
Transient Response Max deviation Recovery to within ± 1%	- -	150 mV 50 uS	250 mV 100 uS	di/dt = 0.1 A/uS, V _{in} = 48 V T _a = 25 °C, 25% load change.

General Specifications



Parameter	Min	Typ	Max	Notes
Switching Frequency	-	96 kHz	-	fixed
Weight	-	TBD	-	
Operating Temperature	-40 °C	-	70 °C	
Non-Operating Temperature	-55 °C	-	125 °C	
Overtemp Shutdown	-	120 °C	-	10 °C hysteresis measured on Q4
Dimensions Inches (L × W × H) Millimeters (L × W × H)		2.28 x 1.45 x 0.50 57.9 x 36.8 x 12.7		
Protection Features Short circuit Over current Undervoltage Overvoltage		Latching 110% to 125% max I _o UVLO V _{in} < 35.0 OVSD V _{in} > 57.0		
Remote On/Off Active Low (Optional Active High) Turn on delay Output voltage rise time	0 V 1.0 V - -	- - 2.7 ms 4.3 ms	0.4 V 18 V - -	
Safety Agency Approvals (pending)	UL / cUL Recognized Certified to EN60950			

ISOLATED DC/DC CONVERTERS

48 VDC Input 12 VDC/27 A Output, 1/4 Brick

bel
POWER PRODUCTS

Mechanical Drawing



Pin Connections

Pin	Function
1	+ Vin
2	Remote On/Off
3	- Vin
4	- Vout
5	+ Vout

RoHS Compliance

Complies with the European Directive 2002/95/EC, calling for the elimination of lead and other hazardous substances from electronic products.



©2008 Bel Fuse Inc. Specifications subject to change without notice. 110308

CORPORATE

Bel Fuse Inc.
206 Van Vorst Street
Jersey City, NJ 07302
Tel 201-432-0463
Fax 201-432-9542
www.belfuse.com

FAR EAST

Bel Fuse Ltd.
8F/ 8 Luk Hop Street
San Po Kong
Kowloon, Hong Kong
Tel 852-2328-5515
Fax 852-2352-3706
www.belfuse.com

EUROPE

Bel Fuse Europe Ltd.
Preston Technology Management Centre
Marsh Lane, Suite G7, Preston
Lancashire, PR1 8UD, U.K.
Tel 44-1772-556601
Fax 44-1772-888366
www.belfuse.com