


## Dual Boost chopper NPT IGBT Power Module

$V_{CES} = 600V$   
 $I_C = 90A @ T_c = 80^\circ C$




### Application

- AC and DC motor control
- Switched Mode Power Supplies
- Power Factor Correction (PFC)
- Interleaved PFC

### Features

- Non Punch Through (NPT) Fast IGBT
  - Low voltage drop
  - Low tail current
  - Switching frequency up to 100 kHz
  - Soft recovery parallel diodes
  - Low diode VF
  - Low leakage current
  - RBSOA and SCSOA rated
  - Symmetrical design
- Kelvin emitter for easy drive
- Very low stray inductance
- High level of integration
- Internal thermistor for temperature monitoring



All multiple inputs and outputs must be shorted together  
 Example: 13/14 ; 29/30 ; 22/23 ...

### Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- Easy paralleling due to positive TC of VCEsat
- Each leg can be easily paralleled to achieve a single boost of twice the current capability
- RoHS compliant

### Absolute maximum ratings

| Symbol    | Parameter                             | Max ratings         | Unit        |
|-----------|---------------------------------------|---------------------|-------------|
| $V_{CES}$ | Collector - Emitter Breakdown Voltage | 600                 | V           |
| $I_C$     | Continuous Collector Current          | $T_c = 25^\circ C$  | 110         |
|           |                                       | $T_c = 80^\circ C$  | 90          |
| $I_{CM}$  | Pulsed Collector Current              | $T_c = 25^\circ C$  | 200         |
| $V_{GE}$  | Gate - Emitter Voltage                | $\pm 20$            | V           |
| $P_D$     | Maximum Power Dissipation             | $T_c = 25^\circ C$  | 416         |
| RBSOA     | Reverse Bias Safe Operating Area      | $T_j = 150^\circ C$ | 200A @ 600V |

**CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on [www.microsemi.com](http://www.microsemi.com)

All ratings @  $T_j = 25^\circ\text{C}$  unless otherwise specified

**Electrical Characteristics**

| Symbol        | Characteristic                       | Test Conditions                              | Min                       | Typ | Max | Unit          |
|---------------|--------------------------------------|--|---------------------------|-----|-----|---------------|
| $I_{CES}$     | Zero Gate Voltage Collector Current  | $V_{GE} = 0\text{V}, V_{CE} = 600\text{V}$   |                           |     | 250 | $\mu\text{A}$ |
| $V_{CE(sat)}$ | Collector Emitter Saturation Voltage | $V_{GE} = 15\text{V}$<br>$I_C = 100\text{A}$ | $T_j = 25^\circ\text{C}$  | 2   | 2.5 | V             |
|               |                                      |  | $T_j = 125^\circ\text{C}$ | 2.2 |     |               |
| $V_{GE(th)}$  | Gate Threshold Voltage               | $V_{GE} = V_{CE}, I_C = 1.5\text{mA}$        | 4.5                       | 5.5 | 6.5 | V             |
| $I_{GES}$     | Gate – Emitter Leakage Current       | $V_{GE} = 20\text{V}, V_{CE} = 0\text{V}$    |                           |     | 400 | nA            |

**Dynamic Characteristics**

| Symbol       | Characteristic               | Test Conditions  | Min                       | Typ | Max | Unit |
|--------------|------------------------------|--|---------------------------|-----|-----|------|
| $C_{ies}$    | Input Capacitance            | $V_{GE} = 0\text{V}; V_{CE} = 25\text{V}$  |                           | 4.3 |     | nF   |
| $C_{res}$    | Reverse Transfer Capacitance | $f = 1\text{MHz}$  |                           | 0.4 |     |      |
| $Q_G$        | Gate charge                  | $V_{GE} = 15\text{V}; V_{CE} = 300\text{V}$<br>$I_C = 100\text{A}$                                   |                           | 240 |     | nC   |
| $T_{d(on)}$  | Turn-on Delay Time           | Inductive Switching ( $25^\circ\text{C}$ )   |                           | 25  |     | ns   |
| $T_r$        | Rise Time                    | $V_{GE} = \pm 15\text{V}$<br>$V_{Bus} = 300\text{V}$   |                           | 10  |     |      |
| $T_{d(off)}$ | Turn-off Delay Time          | $I_C = 100\text{A}$  |                           | 130 |     |      |
| $T_f$        | Fall Time                    | $R_G = 2.2\Omega$  |                           | 20  |     |      |
| $T_{d(on)}$  | Turn-on Delay Time           | Inductive Switching ( $125^\circ\text{C}$ )  |                           | 25  |     | ns   |
| $T_r$        | Rise Time                    | $V_{GE} = \pm 15\text{V}$<br>$V_{Bus} = 300\text{V}$   |                           | 11  |     |      |
| $T_{d(off)}$ | Turn-off Delay Time          | $I_C = 100\text{A}$  |                           | 150 |     |      |
| $T_f$        | Fall Time                    | $R_G = 2.2\Omega$  |                           | 30  |     |      |
| $E_{on}$     | Turn-on Switching Energy     | $V_{GE} = \pm 15\text{V}$<br>$V_{Bus} = 300\text{V}$<br>$I_C = 100\text{A}$                          | $T_j = 125^\circ\text{C}$ | 1   |     | mJ   |
| $E_{off}$    | Turn-off Switching Energy    | $R_G = 2.2\Omega$  | $T_j = 125^\circ\text{C}$ | 3   |     |      |
| $I_{sc}$     | Short Circuit data           | $V_{GE} \leq 15\text{V}; V_{Bus} = 360\text{V}$<br>$t_p \leq 10\mu\text{s}; T_j = 125^\circ\text{C}$ |                           | 450 |     | A    |

**Chopper diode ratings and characteristics**

| Symbol    | Characteristic                          | Test Conditions                            | Min                       | Typ  | Max | Unit          |
|-----------|---|--|---------------------------|------|-----|---------------|
| $V_{RRM}$ | Maximum Peak Repetitive Reverse Voltage |  | 600                       |      |     | V             |
| $I_{RM}$  | Maximum Reverse Leakage Current         | $V_R = 600\text{V}$                        | $T_j = 25^\circ\text{C}$  |      | 100 | $\mu\text{A}$ |
|           |   |  | $T_j = 125^\circ\text{C}$ |      | 500 |               |
| $I_F$     | DC Forward Current                      |  | $T_c = 80^\circ\text{C}$  | 100  |     | A             |
| $V_F$     | Diode Forward Voltage                   | $I_F = 100\text{A}$                        |                           | 1.6  | 2   | V             |
|           |   | $I_F = 200\text{A}$                        |                           | 2    |     |               |
|           |   | $I_F = 100\text{A}$                        | $T_j = 125^\circ\text{C}$ | 1.3  |     |               |
| $t_{rr}$  | Reverse Recovery Time                   | $I_F = 100\text{A}$<br>$V_R = 400\text{V}$ | $T_j = 25^\circ\text{C}$  | 160  |     | ns            |
|           |   |  | $T_j = 125^\circ\text{C}$ | 220  |     |               |
| $Q_{rr}$  | Reverse Recovery Charge                 | $di/dt = 200\text{A}/\mu\text{s}$          | $T_j = 25^\circ\text{C}$  | 290  |     | nC            |
|           |   |  | $T_j = 125^\circ\text{C}$ | 1530 |     |               |

**Temperature sensor NTC** (see application note APT0406 on [www.microsemi.com](http://www.microsemi.com) for more information).

| Symbol                            | Characteristic             | Min | Typ  | Max | Unit |
|-----------------------------------|----------------------------|-----|------|-----|------|
| R <sub>25</sub>                   | Resistance @ 25°C          |     | 50   |     | kΩ   |
| ΔR <sub>25</sub> /R <sub>25</sub> |                            |     | 5    |     | %    |
| B <sub>25/85</sub>                | T <sub>25</sub> = 298.15 K |     | 3952 |     | K    |
| ΔB/B                              | T <sub>C</sub> = 100°C     |     | 4    |     | %    |


$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]}$$

T: Thermistor temperature  
 R<sub>T</sub>: Thermistor value at T

## Thermal and package characteristics


| Symbol            | Characteristic  | Min           | Typ | Max  | Unit |     |
|-------------------|---|---------------|-----|------|------|-----|
| R <sub>thJC</sub> | Junction to Case Thermal Resistance   | IGBT          |     | 0.3  | °C/W |     |
|                   |   | Chopper Diode |     | 0.55 |      |     |
| V <sub>ISOL</sub> | RMS Isolation Voltage, any terminal to case t = 1 min, I <sub>isol</sub> < 1mA, 50/60Hz | 4000          |     |      | V    |     |
| T <sub>J</sub>    | Operating junction temperature range  | -40           |     | 150  | °C   |     |
| T <sub>STG</sub>  | Storage Temperature Range   | -40           |     | 125  |      |     |
| T <sub>C</sub>    | Operating Case Temperature  | -40           |     | 100  |      |     |
| Torque            | Mounting torque   | To heatsink   | M4  | 2.5  | 4.7  | N.m |
| Wt                | Package Weight  |               |     |      | 110  | g   |




## SP3 Package outline (dimensions in mm)



See application note 1901 - Mounting Instructions for SP3 Power Modules on [www.microsemi.com](http://www.microsemi.com)

## Typical IGBT Performance Curve





Microsemi reserves the right to change, without notice, the specifications and information contained herein

Microsemi's products are covered by one or more of U.S patents 4,895,810 5,045,903 5,089,434 5,182,234 5,019,522 5,262,336 6,503,786 5,256,583 4,748,103 5,283,202 5,231,474 5,434,095 5,528,058 6,939,743 7,352,045 5,283,201 5,801,417 5,648,283 7,196,634 6,664,594 7,157,886 6,939,743 7,342,262 and foreign patents. U.S and Foreign patents pending. All Rights Reserved.