1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



Datasheet for 76650-0160

General Information

Part Number: 76650-0160

Manufacturer: Molex / Waldom

Title: Sabre Power Connector Kit

Description: Free Hanging Plug and Receptacle

Product Family: Sabre™

Certificates: (Molex Parts within this kit) - EU RoHS Compliant, UL and CSA

Country of Origin: Kit assembled in U.S.A.

Specifications

Design

Configuration: Wire to Wire

Pitch: 7.5mm (.295")

Connector Type: Receptacles and Plugs

Circuit Sizes: 2, 3, 4, 5 and 6

Current Rating: 12-18 Amps Max. - Dependant on circuit size and wire gauge

Voltage: 600 Volts
Wire size: 18-14 AWG

Product Highlights

The Sabre housings provide a lower-cost option to compete with connectors offering a similar voltage and current rating. The Sabre system is a robust, high-power connector, supplying up to 18 amperes per circuit. The Sabre power-connector system provides design flexibility by accepting a wide range of wire gauges and insulation thicknesses. Lower-flammability Sabre products continue low-cost, high-power connector system legacy.



Datasheet for 76650-0160

Features and Benefits

- Patented new integral Terminal Position Assurance (TPA) on male and female terminal virtually eliminates terminal backout
- Polarized housing assures proper mating
- Positive latch reduces accidental disengagement from mate
- Terminals are fully isolated in housing
- Blade-terminal design has four points of electrical contact, provides a more reliable electrical connection than circular style terminals
- Current rating up to 18.0A at 600V for highcurrent and high-voltage applications

Applications

- Residential or commercial appliances
- HVAC equipment
- Computer servers
- Networking equipment
- Office equipment
- Fitness equipment
- Medical equipment
- Retail Security Scanning Systems
- Home Entertainment
- Factory Automation Equipment
- Lighting
- Power Supplies
- Work Stations
- Automotive Aftermarket

Bill of Materials for Part No. 76650-0160

Molex Part No.	Country of Origin	Description	Quantity in Kit
	or origin	Male Crimp Sabre™ Terminal (18-14) AWG 4.57mm (.180")	1414
43178-2002-C^	USA	max. Ins. Dia.	100
		Female Crimp Sabre™ Terminal (18-14) AWG 4.57mm	
43375-1001-C^	USA	(.180") max. Ins. Dia.	100
44441-2002	USA	2 Circuit 7.5mm (.295") Pitch Sabre™ Receptacle	8
44441-2003	USA	3 Circuit 7.5mm (.295") Pitch Sabre™ Receptacle	5
44441-2004	USA	4 Circuit 7.5mm (.295") Pitch Sabre™ Receptacle	4
44441-2005	USA	5 Circuit 7.5mm (.295") Pitch Sabre™ Receptacle	3
44441-2006	USA	6 Circuit 7.5mm (.295") Pitch Sabre™ Receptacle	3
43680-2002	USA	2 Circuit 7.5mm (.295") Pitch Sabre™ Plug	8
43680-2003	USA	3 Circuit 7.5mm (.295") Pitch Sabre™ Plug	5
43680-2004	USA	4 Circuit 7.5mm (.295") Pitch Sabre™ Plug	4
43680-2005	USA	5 Circuit 7.5mm (.295") Pitch Sabre™ Plug	3
43680-2006	USA	6 Circuit 7.5mm (.295") Pitch Sabre™ Plug	3

[^] Accommodates single or double wire crimps

Recommended Molex Tool(s) for Part No. 76650-0160*

Country

Molex Part No.	of Origin	Description
63811-2100 *	Germany	Hand Crimp Tool for Male Terminal
63813-0600 *	USA	Manual Activation and Deactivation Tool for Male Terminal

1801 Morgan Street Rockford, Illinois 61102 800-435-2931 www.molexkits.com



Datasheet for 76650-0160

63813-0800 *	USA	Manual Extraction Tool for Male Terminal
63813-2700 *	USA	Extraction Tool for Female Terminal
63811-7300 *	Germany	Hand Crimp Tool for Female Terminal

^{*}Tool(s) not included in kit. Tool(s) ordered separately.