

## TCA4 Series TCVCXO Oscillator

Feb 2006



- Pletronics' TCA4 Series is a temperature compensated voltage controlled crystal oscillator with a clipped sinewave output.
- The package is designed for high density surface mount designs.
- Tape and Reel packaging is available.
- 10 to 26 MHz
- 5 x 7 mm LCC Ceramic Package
- Optional Voltage Control Function

**Pletronics Inc. certifies this device is in accordance with the RoHS (2002/95/EC) and WEEE (2002/96/EC) directives.**

Pletronics Inc. guarantees the device does not contain the following:  
Cadmium, Hexavalent Chromium, Lead, Mercury, PBB's, PBDE's  
Weight of the Device: 0.3 grams  
Moisture Sensitivity Level: 1 As defined in J-STD-020C  
Second Level Interconnect code: e4

### Absolute Maximum Ratings:

Parameter	Unit
V <sub>CC</sub> Supply Voltage	-0.5V to +6.5V
V <sub>i</sub> Input Voltage	-0.5V to V <sub>CC</sub> + 0.5V
V <sub>o</sub> Output Voltage	-0.5V to V <sub>CC</sub> + 0.5V

### Thermal Characteristics

The maximum die or junction temperature is 155°C  
The thermal resistance junction to board is 30 to 50°C/Watt depending on the solder pads, ground plane and construction of the PCB.

**Part Number:**

TCA4	027	050	G	H	015	008	-12.75M	-XX	Marking
Internal code or blank									
Nominal Frequency in MHz									fff.fff M
Pullability in ppm (Vcontrol) 000 = TCXO only 008 = ± 8 ppm minimum 015 = ± 15 ppm minimum									none
Stability in ppm 010 = ± 1 ppm 015 = ± 1.5 ppm 025 = ± 2.5 ppm									010 015 025
Highest Specified Operating Temperature A = +40°C   E = +60°C   J = +80°C B = +45°C   F = +65°C   K = +85°C C = +50°C   G = +70°C D = +55°C   H = +75°C									A thru K
Lowest Specified Operating Temperature A = +10°C   E = -10°C   J = -30°C B = +5°C   F = -15°C   K = -35°C C = +0°C   G = -20°C   L = -40°C D = -5°C   H = -25°C   M = -45°C									A thru M
Highest Supply Voltage* 050 = 5.0 volts 036 = 3.6 volts									none
Lowest Supply Voltage * 029 = 2.9 volts 027 = 2.7 volts									none
Series (Part Type, Logic & Package)									TC

\* Supply Voltage: Select range between 2.7V and 5.0V with Highest / Lowest ≤ 1.20  
For Example: the part number for 3.3V nominal would be TCA4030036.....

**Part Marking:**

**Tcywwa**  
**fff.fff M**  
**PLHXXX**

Where:    ywwa    = Date code  
            fff.fff    = frequency in MHz  
            P            = Pletronics  
            LH          = Lowest Temp, Highest Temp  
            XXX        = Stability

Due to part size limitations, marking cannot identify complete specifications.  
A Certificate of Conformance will accompany these parts.

## Electrical Specification for specified V<sub>cc</sub> over the specified temperature range

Item	Min	Max	Unit	Condition
Frequency Range	10	26	MHz	
Frequency Accuracy <sup>1</sup>	-2.5	+2.5	ppm	V <sub>control</sub> 1.50 volts if used <sup>2</sup>
Frequency Stability / Supply	-0.2	+0.2	ppm	Load: 10K ohm // 10 pF & V <sub>cc</sub> ± 5%
Output Waveform	Clipped Sinewave			
Output Level	0.8	1.0	V p-p	Load: 10K ohm ± 10% // 10 pF ± 10%
Phase Noise	-	-135	dBc/Hz	Typical at 1 kHz
V Supply Range <sup>1</sup> V <sub>cc</sub>	2.7	5.0	Volts	
Supply Current I <sub>cc</sub>	-	2.0	mA	
Aging	-1.0	+1.0	ppm	Per year
V <sub>control</sub> Range	0.5	2.50	Volts	1.50 volts nominal
Frequency Pullability <sup>1</sup>	-15	+15	ppm	
Operating Temperature Range <sup>1</sup>	-45	+85	°C	
Storage Temperature Range	-55	+95	°C	

<sup>1</sup> Specified by part number

<sup>2</sup> For all supply voltages, load changes, aging for 1 year, shock, vibration and temperatures

## Reliability: Environmental Compliance

Parameter	Condition
Mechanical Shock	MIL-STD-883 Method 2002, Condition A
Vibration	MIL-STD-883 Method 2007, Condition A
Solderability	MIL-STD-883 Method 2003
Thermal Shock	MIL-STD-883 Method 1011, Condition A

## ESD Rating

Model	Minimum Voltage	Conditions
Human Body Model	1500	MIL-STD-883 Method 3115
Charged Device Model	1000	JESD 22-C101

## Package Labeling


Label is 1" x 2.6" (25.4mm x 66.7mm)  
Font is Courier New  
Bar code is 39-Full ASCII

Label is 1" x 2.6" (25.4mm x 66.7mm)  
Font is Arial

 TCA4027050GH015008-12.75M	
Customer P/N:	 12345678
Qty:	 1000
D/C	 TC512SA

<b>Pb Free</b> 2nd LvL Interconnect Category=e4 Max Safe Temp=260C for 10s 2X Max
--

## Mechanical:



	Inches	mm
A	0.276 $\pm$ 0.006	7.00 $\pm$ 0.15
B	0.197 $\pm$ 0.006	5.00 $\pm$ 0.15
C	0.074 $\pm$ 0.006	1.88 $\pm$ 0.15
D <sup>1</sup>	0.038	0.96
E <sup>1</sup>	0.200	5.08
F <sup>1</sup>	0.004	0.10
G <sup>1</sup>	0.039	1.00
H <sup>1</sup>	0.047	1.20
I <sup>1</sup>	0.024	0.60
J <sup>1</sup>	0.004	0.10R
K <sup>1</sup>	0.008	0.020R

Not to Scale

<sup>1</sup> Typical dimensions

### Contacts :

Gold 11.8  $\mu$ mches 0.3  $\mu$ m minimum over Nickel 50 to 350  $\mu$ mches 1.27 to 8.89  $\mu$ m

Pad	Function	Note
1	Vcontrol Input	If this function is not specified, recommend connecting this pad to ground.
2	Ground (GND)	
3	Output	
4	Supply Voltage (V <sub>CC</sub> )	Recommend connecting appropriate power supply bypass capacitors as close as possible.


## Layout and application information



For Optimum Jitter Performance, Pletronics recommends:

- a ground plane under the device
- no large transient signals (both current and voltage) should be routed under the device
- do not layout near a large magnetic field such as a high frequency switching power supply
- do not place near piezoelectric buzzers or mechanical fans.

## Reflow Cycle (typical for lead free processing)





The part may be reflowed 2 times without degradation.

## Tape and Reel: available for quantities of 250 to 1000 per reel

Constant Dimensions Table 1								
Tape Size	D0	D1 Min	E1	P0	P2	S1 Min	T Max	T1 Max
8mm	1.5	1.0	1.75	4.0	2.0 ±0.05	0.6	0.6	0.1
12mm		1.5			2.0 ±0.1			
16mm		+0.1 -0.0			1.5			
24mm		1.5			1.5			

Variable Dimensions Table 2							
Tape Size	B1 Max	E2 Min	F	P1	T2 Max	W Max	Ao, Bo & Ko
16 mm	12.1	14.25	7.5 ±0.1	8.0 ±0.1	8.0	16.3	Note 1

Note 1: Embossed cavity to conform to EIA-481-B      Dimensions in mm      Not to scale



		REEL DIMENSIONS			
A	inches	7.0	10.0	13.0	Tape Width
	mm	177.8	254.0	330.2	
B	inches	2.50	4.00	3.75	Tape Width
	mm	63.5	101.6	95.3	
C	mm	13.0 +0.5 / -0.2			Tape Width
D	mm	16.4 +2.0 -0.0	16.4 +2.0 -0.0	16.4 +2.0 -0.0	16.0
	mm	---	---	24.4 +2.0 -0.0	24.0
	mm	---	---	32.4 +2.0 -0.0	32.0

Reel dimensions may vary from the above

## IMPORTANT NOTICE

Pletronics Incorporated (PLE) reserves the right to make corrections, improvements, modifications and other changes to this product at anytime. PLE reserves the right to discontinue any product or service without notice. Customers are responsible for obtaining the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to PLE's terms and conditions of sale supplied at the time of order acknowledgment.

PLE warrants performance of this product to the specifications applicable at the time of sale in accordance with PLE's limited warranty. Testing and other quality control techniques are used to the extent PLE deems necessary to support this warranty. Except where mandated by specific contractual documents, testing of all parameters of each product is not necessarily performed.

PLE assumes no liability for application assistance or customer product design. Customers are responsible for their products and applications using PLE components. To minimize the risks associated with the customer products and applications, customers should provide adequate design and operating safeguards.

PLE products are not designed, intended, authorized or warranted to be suitable for use in life support applications, devices or systems or other critical applications that may involve potential risks of death, personal injury or severe property or environmental damage. Inclusion of PLE products in such applications is understood to be fully at the risk of the customer. Use of PLE products in such applications requires the written approval of an appropriate PLE officer. Questions concerning potential risk applications should be directed to PLE.

PLE does not warrant or represent that any license, either express or implied, is granted under any PLE patent right, copyright, artwork or other intellectual property right relating to any combination, machine or process which PLE product or services are used. Information published by PLE regarding third-party products or services does not constitute a license from PLE to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from PLE under the patents or other intellectual property of PLE.

Reproduction of information in PLE data sheets or web site is permissible only if the reproduction is without alteration and is accompanied by associated warranties, conditions, limitations and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. PLE is not responsible or liable for such altered documents.

Resale of PLE products or services with statements different from or beyond the parameters stated by PLE for that product or service voids all express and implied warranties for the associated PLE product or service and is an unfair or deceptive business practice. PLE is not responsible for any such statements.

### Contacting Pletronics Inc.

Pletronics Inc.  
19013 36<sup>th</sup> Ave. W, Suite H  
Lynnwood, WA 98036-5761 USA

Tel: 425-776-1880  
Fax: 425-776-2760  
E-mail: [ple-sales@pletronics.com](mailto:ple-sales@pletronics.com)  
URL: [www.pletronics.com](http://www.pletronics.com)

Copyright © 2005, 2006, Pletronics Inc.