


Rectifier Diode SXXHFN/HFR400





Symbol	Characteristics	Conditions	T _J (°C)	Value	Unit
BLOCKING PARAMETERS					
V _{RRM}	Repetitive peak reverse voltage		180	200-1500	V
I _{RRM}	Repetitive peak reverse current	V = V _{RRM}	180	50	mA
CONDUCTING PARAMETERS					
I _{F(AV)}	Average on-state current	180 sine, 50Hz, T _C = 125°C		400	A
I _{RMS}	RMS on-state current			628	A
I _{FSM}	Non repetitive peak surge on-state current	Sine wave, 10mS without reverse voltage	180	7000	A
I ² t	Permissible surge energy			245	kA ² S
V _{FM}	Peak on-state voltage drop	On-state current = 1050A	180	1.12	V
V ₀	Typical forward conduction Threshold voltage		180	0.75	V
r ₀	Typical forward slope resistance		180	0.35	mΩ
THERMAL & MECHANICAL PARAMETERS					
R _{TH(J-C)}	Thermal impedance, 180° conduction, Sine	Junction to case		0.11	°C/W
R _{TH(C-HK)}	Thermal impedance	Case to heatsink		0.02	°C/W
T _J	Maximum Permissible junction temperature			180	°C
T _{STG}	Storage temperature range			-40 – 180	°C
F	Mounting Torque			20	NM
W	Weight			350	gms




HIND RECTIFIERS LTD

Rectifier Diode SXXHFN/HFR400




All dimensions in mm


On State Power Loss




HIND RECTIFIERS LTD




Maximum Permissible Case Temp




Max non repetitive Surge Current







Transient Thermal Impedance Junction to Case



On State Characteristics



Rectifier Diode SXXHFN/HFR400



Ordering Information: -

S	XX	HFN / HFR	400
Hirect make Rectifier Diode	$V_{RRM} = XX * 100$ e.g.12 * 100 =1200V	HFN – Normal Polarity HFR – Reverse Polarity	$I_{F(AV)} = 400A$

Hind Rectifiers Ltd reserves the right to change the specifications without notice.

This datasheet specifies technical information for semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.

Hind Rectifiers Ltd

Lake Road

Bhandup (West)

Mumbai – 400 078

Tel: - +91 22 2596 8027/28/29/31

Fax: - +91 22 2596 4114

E-mail: - marketing@hirect.com

Website: - www.hirect.com

June-2008



HIND RECTIFIERS LTD

5 of 5