



APPLICATIONS

Wireless Network
Telecom/Datacom
Industry Control System
Distributed Power Architectures
Semiconductor Equipment
Microprocessor Power Applications

FEATURES

- OUTPUT CURRENT UP TO 6A
- SMALL SIZE AND LOW PROFILE :
0.80" X 0.45" X 0.22" (SMD) ; 0.9" X 0.40" X 0.20" (SIP)
- HIGH EFFICIENCY - 94% @ 3.3V FULL LOAD
- INPUT RANGE FROM 2.4VDC TO 5.5VDC
- FIXED SWITCHING FREQUENCY (300KHZ)
- SMD & SIP PACKAGES
- OUTPUT VOLTAGE PROGRAMMABLE FROM 0.75VDC TO 3.3VDC VIA EXTERNAL RESISTOR
- INPUT UNDER-VOLTAGE LOCKOUT
- UL60950-1, EN60950-1 AND IEC60950-1 LICENSED
- ISO9001 CERTIFIED MANUFACTURING FACILITIES
- COMPLIANT TO RoHS EU DIRECTIVE 2002/95/EC

1 / 3

OPTIONS

Positive Logic Remote on/off

DESCRIPTION

DOS06-05T (SMD type), DOH06-05T (for Vertical Mounting SIP type) and DOH06-05TA (for Horizontal Mounting SIP type) are non-isolated DC/DC converters that can deliver up to 6A of output current with full load efficiency of 94% at 3.3V output.

TECHNICAL SPECIFICATION

All specifications are typical at nominal input, full load and 25°C otherwise noted

OUTPUT SPECIFICATIONS			INPUT SPECIFICATIONS		
Output current	6A max.		Input voltage range	Vo(set) < Vin – 0.5V	2.4 – 5.5VDC
Voltage accuracy	Full load and Vin(nom.)	± 2%Vo(set)	Maximum input current	Vin=Vin(min.); Vo(set)=3.3V; Io=Io(max.)	6A
Minimum load		0%	Input filter (Note 5)		C filter
Line regulation	Vin=Vo(set)+0.5V to Vin(max.) at Full Load	± 0.3%Vo(set),typ.	Input no load current	Vo(set) =0.75Vdc (Vin=5V, Io=0, module enabled)	20mA,typ. 45mA,typ.
Load regulation	No Load to Full Load	± 0.4%Vo(set),typ.	Input under voltage lockout	Start-up voltage	2.2V,typ.
Ripple and noise (Note2)	20MHz bandwidth	20mVrms,max. 50mVp-p,max.	Shutdown voltage	Shutdown voltage	2.0V,typ.
Temperature coefficient		±0.4%, typ.	Input reflected ripple current	5~20MHz, 1μH source impedance	35mAp-p
Dynamic load response (Note2)	△Io / △t = 2.5A/μS ,Vin(nom.) Peak deviation Load change step (50% to 100% or 100% to 50% of Io(max.))	130mV,typ. Setting time (Vo<10%peak deviation)	Operating ambient temperature	–40°C ~ +85°C (with derating)	
Dynamic load response (Note3)	△Io / △t = 2.5A/μS ,Vin(nom) Load change step (50% to 100% or 100% to 50% of Io(max.))	50mV,typ. Setting time (Vo<10%peak deviation)	Storage temperature range	–55°C ~ +125°C	
Output current limit		220%,typ.	Thermal shock	MIL-STD-810F	
Output short-circuit current		Hiccup, automatics recovery	Over temperature protection	135 °C, typ.	
External load capacitance	ESR ≥ 1mΩ ESR ≥ 10mΩ	1000μF,max. 3000μF,max.	ENVIRONMENTAL SPECIFICATIONS		
Output voltage overshoot-startup	Vin=2.4~5.5V, F.L.	1%Vo(set)	Operating ambient temperature	–40°C ~ +85°C (with derating)	
Voltage adjustability (see fig.1)	(Note 4)	0.7525V ~ 3.63V	Storage temperature range	–55°C ~ +125°C	
GENERAL SPECIFICATIONS			Thermal shock	MIL-STD-810F	
Efficiency		See table	Over temperature protection	135 °C, typ.	
Isolation voltage		None	ENVIRONMENTAL SPECIFICATIONS		
Switching frequency		300KHz, typ.	Operating ambient temperature	–40°C ~ +85°C (with derating)	
Approvals and standard	IEC60950-1, UL60950-1, EN60950-1		Storage temperature range	–55°C ~ +125°C	
Dimensions	SMD (20.3 X 11.4 X 5.5 mm)	0.80 X 0.45 X 0.22 Inch (20.3 X 11.4 X 5.5 mm)	Thermal shock	MIL-STD-810F	
Weight		2.8g(0.1oz)	Over temperature protection	135 °C, typ.	
MTBF (Note 1)	BELLCORE TR-NWT-000332 MIL-HDBK-217F	2.133 x 10 ⁷ hrs 3.247 x 10 ⁶ hrs	FEATURE SPECIFICATIONS		





**POWER MATE
TECHNOLOGY CO.,LTD.**

DOS06-05T Non-isolated
DOH06-05T Point of load DC/DC converters

2 / 3

Model Name	ON/OFF Logic	Package	Input Voltage	Output Voltage	Output Current		Efficiency (%) 5.0Vin, 3.3Vdc@6A
					Min. Load	Max. Load	
DOS06-05T	Negative	SMD					
DOH06-05T	Negative	Vertical Mounting	2.4 ~ 5.5Vdc	0.75 ~ 3.3Vdc	0A	6A	94%
DOH06-05T-P	Positive	SIP	Vin(min.)=Vo(set)+0.5V				
DOH06-05TA	Negative	Horizontal Mounting					
DOH06-05TA-P	Positive	SIP					

Note

1. BELLCORE TR-NWT-000332. Case 1: 50% Stress, Temperature at 40°C.
2. MIL-HDBK-217F Notice2 @Ta=25 °C, Full load(Ground, Benign, controlled environment).
3. External with $C_{out} = 1\mu F$ ceramic//10μF tantalum capacitors.
4. Output voltage programmable from 0.75V to 3.3V by connecting a single resistor (shown as Rtrim in Table 1) between the TRIM and GND pins of the module. To calculate the value of the resistor **Rtrim** for a particular output voltage **Vo**, use the following equation:

$$R_{trim} = \left[\frac{21070}{V_o - 0.7525} - 5110 \right] \Omega$$

5. It's necessary to equip the external input capacitors at the input of the module. The capacitors should connect as close as possible to the input terminals that ensuring module stability. The external C_{in} is $2 \times 150\mu F$ low-ESR polymer capacitors // $2 \times 47\mu F$ ceramic capacitors at least.
6. Device code with suffix “-P” – Positive logic(On/Off is open collector/drain logic input; Signal referenced to GND)
- Device code with no suffix – Negative logic (On/Off pin is open collector/drain logic input with external pull –up resistor; signal referenced to GND)
7. Case 1 :On/Off input is set to logic low (module on) and then input power is applied (delay from instant at which $Vin=Vin(min)$ until $Vo=10\%$ of $Vo(set)$)
8. Case 2 :Input power is applied for at least one second and then the On/Off input is set to logic low (delay form instant at which $Von/off=0.3V$ until $Vo=10\%$ of $Vo(set)$)

CAUTION: This power module is not internally fused. An input line fuse must always be used.





Fig. 1






Table 1	
Vo(set) (V)	Rtrim (KΩ)
0.7525	Open
1.2	41.973
1.5	23.077
1.8	15.004
2.5	6.974
3.3	3.160







DOH06-05T



DOH06-05TA



DOS06-05T



- All dimensions in Inches (mm)
Tolerance: X.XX±0.02 (X.X±0.5)
X.XXX±0.01 (X.XX±0.25)
- Pin pitch tolerance ±0.01(0.25)
- Pin dimension tolerance ±0.004 (0.1)