



KBPC6005 THRU KBPC610

SINGLE PHASE SILICON BRIDGE RECTIFIER


Reverse Voltage - 50 to 1000 Volts Forward Current - 6.0 Ampere

FEATURES

- Diffused Junction
- Surge overload rating: 125A peak

MECHANICAL DATA

- Case: UL-94 Class V-0 recognized Flame Retardant Epoxy
- Terminals: Plated leads solderable per MIL-STD 202, method 208
- Mounting Position: Any
- Marking: Type Number



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.
Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Characteristic	Symbol	KBPC 6005	KBPC 601	KBPC 602	KBPC 604	KBPC 606	KBPC 608	KBPC 610	Unit
Peak Repetitive Reverse Voltage	V_{RRM}	50	100	200	400	600	800	1000	V
Working Peak Reverse Voltage	V_{RWM}								
DC Blocking Voltage	V_R								
RMS Reverse Voltage	$V_{R(RMS)}$	35	70	140	280	420	560	700	V
Average Rectified Output Current (Note 1) @ $T_C = 50^\circ C$	I_o	6.0							A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}	125							A
Forward Voltage per leg @ $I_F = 3.0A$	V_{FM}	1.1							V
Peak Reverse Current @ $T_A = 25^\circ C$ At Rated DC Blocking Voltage @ $T_A = 125^\circ C$	I_R	5.0 500							μA
I^2t Rating for Fusing ($t < 8.3ms$) (Note 2)	I^2t	64							A^2s
Typical Junction Capacitance (Note 3)	C_j	80							pF
Typical Thermal Resistance per leg (Note 1)	$R_{\theta JC}$	9.5							$^\circ C/W$
Operating and Storage Temperature Range	T_j, T_{STG}	-65 to +125							$^\circ C$

- Note: 1. Mounted on metal chassis.
2. Non-repetitive, for $t > 1ms$ and $< 8.3ms$.
3. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.



KBPC6005 THRU KBPC610

RATINGS AND CHARACTERISTIC CURVES




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Peak Forward Surge Current




Fig. 4 Typical Reverse Characteristics