

CRYSTAL OSCILLATOR SPXO

SG-310 series

- Frequency range : 2 MHz to 48 MHz
- Supply voltage : 1.8 V Typ. / 2.5 V Typ. / 3.3 V Typ.
- Current consumption : SEF1.8 V No load condition 48 MHz
1.5 mA Typ.
- Function : Standby(\overline{ST})
- Thickness : 1.05 mm Typ.



Actual size




Specifications (characteristics)

Item	Symbol	Specifications					Remarks
		SG-310 SEF	SG-310 SDF	SG-310 SCF	SG-310 SDN	SG-310 SCN	
Output frequency range	f_0	2.000 MHz to 48.000 MHz			3.000 MHz to 48.000 MHz		
Supply voltage	V_{CC}	1.8 V Typ. 1.6 V to 2.2 V	2.5 V Typ. 2.2 V to 3.0 V	3.3 V Typ. 2.7 V to 3.6 V	2.5 V Typ. 2.2 V to 2.7 V	3.3 V Typ. 2.7 V to 3.6 V	
Temperature range	Storage temperature	-40 °C to +125 °C					Store as bare product after unpacking
	Operating temperature	-40 °C to +85 °C					
Frequency tolerance	F_{tol} (osc)	B: $\pm 50 \times 10^{-6}$, C: $\pm 100 \times 10^{-6}$			-		-20 °C to +70 °C
		M: $\pm 100 \times 10^{-6}$			-		-40 °C to +85 °C
		-			D: $\pm 20 \times 10^{-6}$, S: $\pm 25 \times 10^{-6}$		-20 °C to +70 °C
		-			R: $\pm 25 \times 10^{-6}$		-30 °C to +85 °C
		-			P: $\pm 20 \times 10^{-6}$		-30 °C to +85 °C
Current consumption	I_{CC}	1.5 mA Max.	1.5 mA Max.	1.5 mA Max.	-		No load condition, 2 MHz < f_0 ≤ 4 MHz
		1.5 mA Max.	1.5 mA Max.	2.0 mA Max.	-		No load condition, 4 MHz < f_0 ≤ 8 MHz
		1.5 mA Max.	2.0 mA Max.	2.5 mA Max.	-		No load condition, 8 MHz < f_0 ≤ 16 MHz
		2.0 mA Max.	2.0 mA Max.	2.5 mA Max.	-		No load condition, 16 MHz < f_0 ≤ 25 MHz
		2.0 mA Max.	2.5 mA Max.	3.5 mA Max.	-		No load condition, 25 MHz < f_0 ≤ 33 MHz
		3.0 mA Max.	3.5 mA Max.	4.5 mA Max.	-		No load condition, 33 MHz < f_0 ≤ 48 MHz
Stand-by current	I_{std}	0.7 μ A Max. (0.2 μ A Typ.)	1.5 μ A Max. (0.5 μ A Typ.)	2.0 μ A Max. (1.0 μ A Typ.)	1.5 μ A Max.	3.0 μ A Max.	\overline{ST} = GND
Symmetry	SYM	45 % to 55 %	45 % to 55 %	45 % to 55 %	45 % to 55 %		2 MHz < f_0 ≤ 16 MHz
		40 % to 60 %	40 % to 60 %	40 % to 60 %	40 % to 60 %		16 MHz < f_0 ≤ 40 MHz
High output voltage	V_{OH}	90 % V_{CC} Min.					I_{OH} = -3 mA
Low output voltage	V_{OL}	10 % V_{CC} Max.					I_{OL} = 3 mA
Output load condition (CMOS)	L_{CMOS}	15 pF Max.					
Output enable / disable input voltage	V_{IH}	80 % V_{CC} Min.			70 % V_{CC} Min.		\overline{ST} terminal
	V_{IL}	20 % V_{CC} Max.			30 % V_{CC} Max.		
Output rise and fall time	tr/ tf	4 ns Max.					20 % V_{CC} to 80 % V_{CC} level, L_{CMOS} = 15 pF
Oscillation start up time	t_{osc}	10 ms Max.			2 ms Max.		t=0 at 90 % V_{CC}
Frequency aging	F_{aging}	$\pm 5 \times 10^{-6}$ / year Max.			$\pm 3 \times 10^{-6}$ / year Max.		+25 °C, First year, V_{CC} = 1.8 V, 2.5 V, 3.3 V

External dimensions

(Unit:mm)



Footprint (Recommended)

(Unit:mm)

