
PCM-3115 PCM-3116


2-slot Card Bus Module

2-slot mini PCI Module



Features

- High-performance (PC/104-Plus)
- Low power consumption (Hardware Suspend)
- Compliant with PC Card 95/97/98, Card-32 (32 Bit), PCMCIA V2.1/JEIDA 4.2 (16 Bit)
- Accepts Type I/II/III PCMCIA cards
- Supports 2 PCMCIA slots (when Type III card used in Slot 2, Slot 1 will be occupied too)



Features

- Supports 2 miniPCI devices
- High performance (PC/104-Plus)
- Compliant with PCI v2.1

Specifications

General

Chipset Ricoh® Card Bus Controller
16-bit Legacy Mode YES (3E0/3E2 I/O port) support

■ GPIO Support YES

• PCI way Legacy DMA YES supported

Data Bus 32-Bit data bus (Compliant with PCI Bus Specification 2.1)

• **PCI Interface** 3.3 V interface (5 V tolerant)

H/W Configuration
S/W Driver
Plug & Play automatic detection & configuration
Supports Windows® NT 4.0, Windows® 95/98/2000

Mechanical and Environmental

Dimension (L x W) 96 x 90 mm (3.8" x 3.5")
Weight 0.094 kg (0.207 lb)

■ **Temperature** Operating: 0 ~ 60° C (32 ~ 140° F) Storage: -40 ~ 85° C (-40 ~ 185° F)

• **Operating Humidity** 0% ~ 90% relative humidity, non-condensing

Power

■ Power Supply Voltage +5 V, ± 5 % tolerance on power supply

■ Power Consumption +5 V @ 70 mA (typical)

Packing List

- 1 x Startup manual
- 1 x CD-ROM (Manual, Driver, Utility)
- 1 x PCM-3115

Ordering Information

Standard

• PCM-3115-00B1E 2-slot Card Bus module

Specifications

General

Data Bus
32-Bit data bus (Compliant with PCI Bus Specification 2.1)

• **PCI Interface** 3.3 V interface (5 V tolerant)

Mechanical and Environmental

Dimension (L x W) 96 x 90 mm (3.8" x 3.5")
Weight 0.094 kg (0.207 lb)

■ **Temperature** Operating: 0 ~ 60° C (32 ~ 140° F) Storage: -40 ~ 85° C (-40 ~ 185° F)

• Operating Humidity 0% ~ 90% relative humidity, non-condensing

Power

■ Power Supply Voltage +5 V, ± 5 % tolerance on power supply

Packing List

1 x Startup manual

■ 1 x PCM-3116

Ordering Information

Standard

PCM-3116-00A1E 2-slot miniPCI module