

CRO Product Specification

 Model:
 CR0190-1280T
 Rev:
 P2
 Date:
 10/27/2004

 Customer:
 SIRENZA MICRODEVICES

Operating Temperature Range: (-40 ° to 85 ° C)

Parameter	Min	Тур	Max	Units	Х	Remarks
Frequency Range -	1240		1320	MHz	Х	
Tuning Voltage:						
1240 MHz	1	1.5		Vdc	Х	
1320 MHz		14	18	Vdc	Х	
Tuning Sensitivity -	2	7	14	MHz/V	Х	
Output Power -	1	4	7	dBm	Х	
Output Phase Noise:						
1 kHz		-88	-83	dBc/Hz		
10 kHz		-114	-109	dBc/Hz		
100 kHz		-135	-130	dBc/Hz		
1000 kHz		-155	-150	dBc/Hz		
Power Supply -	4.9	5	5.1	Volts		
Supply Current -		25	30	mA	Х	
Harmonic Suppression:						
2nd Harmonic		-25	-10	dBc	Х	
3rd Harmonic		-25	-10	dBc	Х	
Spurious (Non-Harmonic) -			-90	dBc		
Frequency Pushing - 4.9-5.1 V		0.2	0.5	MHz p-p		
Frequency Pulling - into a 12 dB RL		1.7	3	MHz p-p		
Tuning Port Capacitance -		68		рF		
Output Impedance -		50		Ω		

Package Information

Package Type:	Т	Drawing Number:	60035
Dimensions:	0.5 x 0.5 x 0.223 inches	Drawing Revision:	D

Comments

X Indicates parameter to be tested 100% in production

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza Microdevices' products are subject to change without notice. Buyers should consult Sirenza Microdevices' standard terms and conditions of sale for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices and/or systems.

Page 1 of 1

303 S. Technology Ct.

tel 303.327.3030