


Product Features

- GaAs MESFET + InGaP HBT
- No matching circuit needed
- High IP3
- Surface Mount Hybrid Type & Reel Packing
- Small Size
- Alumina Substrate

Applications

- PCS Repeater
- RF Sub-Systems
- Base Station



Package : CP-16B

Descriptions

It is one of the smallest matched Amplifiers.

This family of High gain Linear Amplifier has superior performance comes with a modest price tag

Electrical Characteristics

Absolute Minimum and Maximum Ratings

PARAMETER	UNIT	MIN	MAX
Device Voltage	VDC		+6
RF Input Power	dBm		+7
Storage Temperature	°C	-40	+125

Operating Ranges

PARAMETER	UNIT	MIN	TYP	MAX
Operating Frequency	MHz	2400		2600
Device Voltage	VDC		+5	+5.3
Case Temperature	°C	-40		+85

Electrical Specifications

(Ta=+25 °C, V_{DD}=+5V, Fc=2500 MHz)


PARAMETER	UNIT	MIN	TYP	MAX
Gain	dB	25.5	26.5	
Input Return Loss	dB		-15	
Output Return Loss	dB		-15	
Output IP3	dBm	+38	+41	
1dB Compression Point	dBm		+21.5	
Noise Figure	dB		5.6	
DC Current	mA	170	200	230
Supply Voltage	VDC		+5	

OIP3 is measured with two tones, at an output power of 10dBm/tone separated by 1MHz


Performance Charts ($V_d=5V, I_d=200mA, T_c=25^\circ C$)

Frequency	MHz	2400	2440	2480	2520	2560	2600
Gain	dB	27.5	27.2	26.8	26.5	26	25.5
S11	dB	-14	-14.5	-15.5	-16	-17	-18
S22	dB	-18	-17	-15.5	-14	-13	-12
OIP3	dBm	41	41.5	42	41.5	42	42
P1dB	dBm	21.5	21.4	21.5	21.5	21.4	21.5
Noise Figure	dB	5.6	5.6	5.6	5.6	5.6	5.6


S-Parameter vs. Frequency




OIP3 vs. Frequency





Noise Figure vs. Frequency



P1dB vs. Frequency



Package Dimensions (Type: CP-16B)



Same Package Platform for Below Part Numbers

GLM0921-L / GLM1521-L / GLM1821-L / GLM2121-L
 GLM2521-L / GLM2123-L / GLM2523-L / GLM2723-L
 GLM3623-L / 2LM0905-L / 2LM2105-L

RFHIC Corporation (RFHIC) reserves the right to make changes to any products herein or to discontinue any product at any time without notice. RFHIC do not assume any liability for the suitability of its products for any particular purpose, and disclaims any and all liability, including without limitation consequential or incidental damages. The product specifications herein expressed have been carefully checked and are assumed to be reliable. However, RFHIC disclaims liability for inaccuracies and strongly recommends buyers to verify that the information they are using is current before placing purchase orders. RFHIC products are not intended for use in life support equipment or application where malfunction of the product can be expected to result in personal injury or death. Buyer uses or sells such products for any such unintended or unauthorized application, buyer shall indemnify, protect and hold RFHIC and its directors, officers, stockholders, employees, representatives and distributors harmless against any and all claims arising out of such use. RFHIC's liability under or arising out of damages, claims of whatsoever kind and nature which RFHIC products could cause shall be limited in amount to the net purchase price of the products sold to buyer by RFHIC.