SPECIFICATION

Product name : Rodan Spark Gap

Type : RSG-502-BKL



Version

First

OKAYA ELECTRIC AMERICA, INC.


| Spec No. | SS-023 |
|----------|--------------|
| Data | Oct 30, 2003 |

1. Scope This specification covers Rodan Spark Gap RSG-502-BKL.

2. Type designation

First

Version



3. Appearance Structure

3-1 Dimension Refer to drawing 4R-4198-Y85

3-2 Display and contents Marking must not be disappeared easily, and it has to be identified.




Fig.1 Example of marking

3-3 Materials Ceramic, Electrode, Lead wire etc

3-4 Plating treatment Tinning

3-5 Filler gas Ar, mixed gas (This product doesn't use radioisotope.



OKAYA ELECTRIC AMERICA, INC.

| Spec No. SS-023 |
|-------------------|
| Data Oct 30, 2003 |

4. Electrical characteristics

First

Version

| No. | Item | Mark | Т | Standard values | | |
|-----|---------------------------|------|---------------------------------------|---|--------------|--|
| 1 | DC breakdown voltage | Ez | $1~\text{M}\Omega$, $500~\text{V/s}$ | 5000 V ±20 % | | |
| 2 | Insulation resistance | IR | DC100 V | 1000 MΩ Min | | |
| 3 | Electrostatic capacitance | С | 1.0 kHz | 2.0 pF Max | | |
| | Life test | | Switching times | 1 s ON / 10 s OFF | DC breakdown | |
| | | | Ambient temperature | Room temperature | | |
| | | | Test circuit | Voltage 5000 V ⁺²⁰ % | | |
| 4 | | - | R=4 | | | |
| | | | V ₀ =6500 V C=15 | Insulation resistance 100 MΩ Min (DC100 V) | | |
| | | | Minimum numbe according to the a | | | |



| Spec No. | SS-023 |
|----------|--------------|
| Data | Oct 30, 2003 |
| Version | First |

5. Switching frequency

Maximum switching frequency: 200 Hz

6. Operating condition

Operating temperature: -40C to +100C


7. Storage condition

Storage temperature: -40C to +100C

8. About forming

As regards forming of spark gap, please take distance more than 2mm from main body when you bend lead wire.

When performing a forming, please hold only lead wire and be careful not to give a stress on main body.








| Spec No. | SS-023 |
|----------|--------------|
| Data | Oct 30, 2003 |
| Version | First |

9. Packing

Put 50 pcs. of RSG series and 1pc. of product label in a vinyl bag of specified size, seal the bag with a heatseal, put bags of quantity required a box, pack and stick product label on the box.







We ight: approx. 2g

| Ver. | Rev. da ta | History of rev. Date | | History of rev. | Da te Sca le | | Product name | |
|------|-----------------------------|----------------------|---------|-----------------|--------------|-----------------------------|--------------|--|
| | | | 2003 .8 | 3.29 | 2:1 | Rodan spark gap |) | |
| | | | | | | Type name Outline dimension | | |
| | OVAVA | | MEDICA | INC | | (Φ8.0 X 7.5) Drawing No. | _) | |
| | OKAYA ELECTRIC MERICA, INC. | | | | | 4 R - 4198 - Y85 | 4 | |