Linear Amplifier

Product Features

- GaAs MESFET + InGaP HBT
- No matching circuit needed
- High IP3
- Surface Mount Hybrid Type & Reel Packing
- Small Size
- Pb Free / RoHS Standard

Descriptions

It is one of the smallest matched Amplifiers.

This family of High gain Linear Amplifier has superior performance comes with a modest price tag

Electrical Characteristics

Absolute Minimum and Maximum Ratings

PARAMETER	UNIT	MIN	MAX
Device Voltage	VDC		+6
RF Input Power	dBm		+7
Storage Temperature	°C	-40	+125

Operating Ranges

PARAMETER	UNIT	MIN	ТҮР	MAX
Operating Frequency	MHz	3200	-	3800
Device Voltage	VDC	-	+5	

Electrical Specifications

(Ta=+25°C, $V_{DD}=+5V$, F=3600MHz)

PARAMETER	UNIT	MIN	ТҮР	MAX
Gain	dB		21.5	
Input Return Loss	dB		-19	
Output Return Loss	dB		-17	
Output IP3	dBm	38	40	
1dB Compression Point	dBm		22	
Noise Figure	dB		5.7	
DC Current	mA		200	
Supply Voltage	VDC		+5	
Thermal Resistance(Rth)	°C/W			

OIP3 is measured with two tones, at an output power of 10dBm/tone separated by 1MHz

PCS Repeater

GLM3623-L

- RF Sub-Systems
- Base Station





Package : CP-16B

• Tel : 82-31-250-5011

Version 6.0

Applications

rfsales@rfhic.com


[•] All specifications may change without notice.




Frequency	MHz	3400	3500	3600	3700	3800
Gain	dB	22.5	21.9	21.5	21	20
S11	dB	-34	-26	-19	-16	-13
S22	dB	-17	-17	-17	-17	-17
OIP3	dBm	40	40	40	40	40
P1dB	dBm	22	22	22	22	22
Noise Figure	dB	5.7	5.7	5.7	5.7	5.7

Performance Charts (V_d=5V, I_d=200mA, T_c=25 °C)


S-Parameter vs. Frequency




OIP3 vs. Frequency



Noise Figure vs. Frequency




P1dB vs. Frequency



- All specifications may change without notice.
- Version 6.0

<u>RFHIC</u>

Package Dimensions (Type: CP-16B)



Same Package Platform for Below Part Numbers

GLM0921-L / GLM1521-L / GBM1821-L / GLM2121-L GLM2521-L / GLM2123-L / GLM2723-L / GLM3623-L 2LM0905-L / 2LM2105-L

RFHIC Corporation (RFHIC) reserves the right to make changes to any products herein or to discontinue any product at any time without notice. RFHIC do not assume any liability for the suitability of its products for any particular purpose, and disclaims any and all liability, including without limitation consequential or incidental damages. The product specifications herein expressed have been carefully checked and are assumed to be reliable. However, RFHIC disclaims liability for inaccuracies and strongly recommends buyers to verify that the information they are using is current before placing purchase orders. RFHIC products are not intended for use in life support equipment or application where malfunction of the product can be expected to result in personal injury or death. Buyer uses or sells such products for any such unintended or unauthorized application, buyer shall indemnify, protect and hold RFHIC and its directors, officers, stockholders, employees, representatives and distributors harmless against any and all claims arising out of such use. RFHIC's liability under or arising out of damages, claims of whatsoever kind and nature which RFHIC products could cause shall be limited in amount to the net purchase price of the products sold to buyer by RFHIC.

• Tel : 82-31-250-5011

rfsales@rfhic.com

All specifications may change without notice.