




■ HIGH VOLTAGE SWITCH MODE APPLICATIONS

High Speed Switching
Suitable for Switching Regulator and Montor Control

■ ABSOLUTE MAXIMUM RATINGS (T_a=25°C)

- T_{stg}—Storage Temperature..... -65~150°C
- T_j—Junction Temperature.....150°C
- P_C—Collector Dissipation.....30W
- V_{CBO}—Collector-Base Voltage.....600V
- V_{CEO}—Collector-Emitter Voltage.....400V
- V_{EBO}—Emitter-Base Voltage.....9V
- I_C—Collector Current.....1.5A



■ ELECTRICAL CHARACTERISTICS (T_a=25°C)

| Symbol | Characteristics | Min | Typ | Max | Unit | Test Conditions |
|------------------|---------------------------------------|-----|-----|-----|------|--|
| BVCBO | Collector-Base Breakdown Voltage | 600 | | | V | I _C =1mA, I _E =0 |
| BVCEO | Collector-Emitter Breakdown Voltage | 400 | | | V | I _C =10mA, I _B =0 |
| BVEBO | Emitter-Base Breakdown Voltage | 9 | | | V | I _E =1mA, I _C =0 |
| HFE | DC Current Gain | 10 | | 40 | | V _{CE} =10V, I _C =0.1A |
| VCE(sat)1 | Collector- Emitter Saturation Voltage | | | 0.8 | V | I _C =1A, I _B =500mA |
| VCE(sat)2 | Collector- Emitter Saturation Voltage | | | 0.8 | V | I _C =0.5A, I _B =100mA |
| VBE(sat) | Base-Emitter Saturation Voltage | | | 1.2 | V | I _C =0.5A, I _B =100mA |
| ICBO | Collector Cut-off Current | | | 10 | μ A | V _{CB} =500V, I _E =0 |
| IEBO | Emitter-Base Cut-off Current | | | 10 | μ A | V _{EB} =9V, I _C =0 |
| f _T | Current Gain-Bandwidth Product | 8 | | | MHz | V _{CE} =10V, I _C =0.1A, f=1MHz |
| t _{ON} | Turn On Time | | | 1.1 | μ s | V _{CC} =125V, I _C =1A, I _{B1} =0.2A, I _{B2} =-0.2A R _L =125 Ω |
| t _{STG} | Storage Time | | | 4.0 | μ s | |
| t _F | Fall Time | | | 0.7 | μ s | |

■ h_{FE} Classification

| H1 | H2 | H3 | H4 | H5 |
|-------|-------|-------|-------|-------|
| 10-16 | 14-21 | 19-26 | 24-31 | 29-40 |

