

MSMFW104EX – Firewall Board with two 1394B & one 1394A Connections
Features

- 2x IEEE1394B (800 MB/s)
- 1x IEEE1394A (400 MB/s)
- PCI-104 Pass Through Connector


Technical Specifications

FEATURE	MSMFW104EX
Part no. (PCIe + PCI)	801752
Function	FireWire IEEE1394B
ISA-BUS	-
PCI-BUS	pass-through PCI-104
PCI Express-BUS	yes 1x lane
BUS compatibility	PCI/104-Express
Controller	TI
PCIe switch	-
1st interface (standard)	1x IEEE1394A
2nd interface (alternative)	2x IEEE1394B
3rd interface	-
Power normal (typ.)	5V 3.3V/1W
Power management	12V
Operating temperature	-25°C to +70°C
Extended operating temperature	-40°C to +70°C
Size (W x L x H in mm)	90 x 96 x 17
Weight	75 g
Software support	WINXP Linux
MTBF	200'000h
Bandwidth (max.)	800/400
Special features 2	-
Special features 3	-
Accessories	

Description

The MICROSPACE® PCI/104-Express MSMFW104EX expansion card has a PCIe FireWire controller which has 2x 1EEE1394B and 1x 1EEE1394A connections.

Ordering Guide

Item Code	Part #	Description
MSMFW104EX	801752	with PC/104+ connector, One 1394A, Two 1394B ports

Data subject to change without notice