



2.5W USB Adapter with Interchangeable Plugs PSC03R Adapter Meets CEC and EISA Requirements



Features

- USB Socket
- Field Changeable AC Plugs
- ECOC Compliance
- Low Leakage Current
- UL 94 Vo Flammability
- Efficiency Level IV Compliance

Applications

- Wireless Communications
- Peripherals
- Portable Equipment
- Networking

Safety Approvals

- cUL/UL
- TUV
- SAA
- CE
- C-Tick

Mechanical Characteristics

- Length: 75.32mm (2.97in)
- Width: 45.96mm (1.81in)
- Height: 31.67mm (1.25in)
- Weight: 61.1g (2.16oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Efficiency Level
		Min.	Max.		Line	Load	
PSC03R-050	5V	0A	0.5A	55mV	±5%		IV

Note: (1) Measured by using a 12-inch twisted pair terminal with a 10uf EC capacitor and a 0.1uf ceramic in parallel, measured at maximum load.

Interchangeable clips sold separately.

Phihong is not responsible for any error and change. Content is subject to change without notice. Please consult the factory and visit www.phihong.com for the most up-to-date specifications.

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Current
0.15A(RMS) max. @ 115VAC
0.08A(RMS) max. @ 230VAC

Leakage Current
20uA max. @ 254VAC, 50Hz

Inrush Current (cold)
<30A for 120VAC at max. load
<60A for 240VAC at max. load
(Cold start @ ambient 25°C)

Input Power Saving
0.5W maximum at no load

OUTPUT:

Efficiency
> 58% average efficiency

Hold-up Time
10mS min. @ 120VAC and Max. load

Over-current Protection
0.75A max.

Over-voltage Protection
8VDC max.

Short Circuit Protection
Output can be shorted without damage

Adapter Detection:
Each data line (Data+ and Data-) is tied to +VDC via a 7.5K Ohm resistor and to DC RTN via a 15K Ohm resistor

ENVIRONMENTAL:

Temperature
Operation 0 to +45°C
Non-operation -40 to +85°C

Humidity
Operation 10 to 90%

Emissions
FCC Part 15 Class B
CISPR 22 Class B

Dielectric Withstand (Hi-pot) Test
Primary to Secondary: 3000VAC

AC Input Clips (sold separately)
US: RPA
Europe: RPE
UK: RPK
Australia: RPS

Dimension Diagram Unit: mm (inch)

