


TYPICAL PERFORMANCE




Horizontal: 2.5 MHz/div

Vertical (from top): Magnitude 10 dB/div
Magnitude 1 dB/div
Group Delay 50 ns/div

SPECIFICATION

Parameter	Min.	Typ.	Max.	Units.
F_visual		38.9		MHz
F_color		32.9		MHz
F_audio		32.4		MHz
Center Frequency (Nominal)		36		MHz
Insertion Loss	28		32	dB
2 dB Lower Band Edge			31.95	MHz
2 dB Upper Band Edge	38.7			MHz
Passband Ripple(32.7 - 38.7)		0.25	0.8	dB p-p
Phase Deviation (32.2 - 38.7)		2.5	8	deg p-p
GD Ripple (32.2 - 38.7)		30	50	ns p-p
Rejection (20 - 31.10)	45	55		dB
Rejection (31.1 - 31.3)	52	60		dB
Rejection (39.4 - 65.0)	45	55		dB
2T K Factor		1		%
C/L Delay - 12.5 T		5		ns
Absolute Delay		4.5		us
Ambient Temperature		40		° C
Temperature Coefficient		-80		ppm / ° C
Source/Load Impedance		50		Ω
Matching Network	None			
Substrate Material	128 Lithium Niobate			

PACKAGE OUTLINE




Units: mm

Pin Configuration:

- Input: 3
- Input Return: 22
- Output: 15
- Output Return: 10
- Ground: All other pins.

MATCHING CIRCUIT



No matching required

