

TR30M Series

20-30 WATTS SINGLE OUTPUT AC/DC MEDICAL

Features

- Wide input voltage 90VAC to 264VAC, 50/60Hz.
- Continuous short circuit protection.
- Over voltage protection.
- Output voltage available from 5VDC to 24VDC.
- High efficiency 75% typical.
- Meets EN60601-1, EN55022 Class "B".



Specifications

INPUT

Voltage Range	90 to 264VAC
Frequency	47Hz to 63Hz
Inrush current	50A max @ 264VAC.
Input current	0.6A.
Isolation	Input to output 5,656VDC.

OUTPUT

Output Voltage	Factory preset, see table (not adjustable)
Voltage Set-Point	+/-2% to +/-4% (60% load)
Ripple and Noise	1% p-p max
Short Circuit Protection	Continuous (Auto recovery)
Over Voltage Protection	Yes.
Hold-up Time	10ms typ @ 115Vac
Load Regulation	+/-2 to +/-6% (20% to 100% load)
Line Regulation	+/-1% max at full load

ENVIRONMENTAL

Operating Temperature	0°C to +40°C
Storage Temperature	-20°C to +85°C

STANDARDS AND APPROVALS

Safety standards	EN60601-1
C-Tick	AS/NZS CISPR11 Group 1, Class A
EMI standards	CISPR/FCC Class B
MEPS compliance	TBC

MECHANICAL

Dimensions	110x50x30mm
Weight	220g
AC Inlet	IEC320/C8.
Output Connector	Right angle, hollow coaxial plug, 2.5mm inside diameter; 5.5mm outside diameter; 9.5mm length Center positive polarity.
DC Cord Length	720mm with ferrite core 18AWG/UL1185.

Selection Table

MODEL NUMBER	RATED Vnom	OUTPUT CURRENT	MAX POWER
TR30M050-21A11	5Vdc	4.0A	20W
TR30M090-21A11	9Vdc	3.0A	27W
TR30M120-21A11	12Vdc	2.5A	30W
TR30M150-21A11	15Vdc	2.0A	30W
TR30M180-21A11	18Vdc	1.65A	30W
TR30M240-21A11	24Vdc	1.25A	30W

Technical Illustration

