



Directive 2002/95/EC
"RoHS"
Compliant

NOTES:

1. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
2. INSULATORS: PBT GF UL 94 V-0; BLACK
3. SIGNAL CONTACTS: COPPER ALLOY; 7,5A nominal
PLATING MATING AREA: 30µm HARD GOLD over min. 50µm NICKEL
FEMALE CONTACTS WIRE BRIDGE FROM POS. 1 TO POS. 2
4. CONNECTOR IS PART MARKED: 13-000201 CONEC ABC

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND				tolerance		 dim. in mm	scale: 2:1		
				date			material: see notes		
				drawn	20.06.07		name	title: Micro TCA Single Port Female, Crimp Style with wire bridge	
				appd.	20.06.07		Koch		
norm									
		d-old		dwg no: Inventor 10	DIN-A3				
a	Origin			13K1A2076					
rev.	description	date	name	part no: 13-000201					



sh: 1