


Strip Block for Snap-in Mounting with 4 IEC Appliance Outlets F and Space for 2 Extra Components



Snap-In Version

**Description**

- Panel Mount:
Snap-in version from front side
- 4 Functions:
Module of 4 outlets, with additional carrier frame for accessory modules, Pin temperature 70 °C, Protection class I
- Solder terminals or quick connect terminals

Approvals

- VDE License Number: 40010521
- UL License Number: E96454
- CSA License Number: 56242

Characteristics

- Busbar is of single piece (no soldering)
- Insulation cover on the rear-side
- Qualified for use in equipment according IEC/EN 60950

Other versions on request

- For protection class II

References

[General Product Information](#)

Weblinks

[Approvals](#), [RoHS](#), [CHINA-RoHS](#), [Mating Connectors](#), [e-Store](#), [SCHURTER-Stock-Check](#), [Distributor-Stock-Check](#)

Technical Data


Ratings IEC	10A / 250VAC; 50Hz
Ratings UL/CSA	15A / 250VAC; 60Hz
Dielectric Strength	> 2kVAC between L-N > 2kVAC between L/N-PE (1 min/50Hz)
Allowable Operation Temp.	-25 °C to 70 °C
Degree of Protection	from front side IP 30 acc. to IEC 60529
Protection Class	Suitable for appliances with protection class 1 acc. to IEC 61140
Terminal	Solder terminals or quick connect terminals
Panel Thickness s	Snap-in 1/ 1.2/ 1.5/ 2/ 2.5/ 3 mm tolerance +0.0/-0.1
Material: Housing	Thermoplastic, black, UL 94V-0

Appliance Outlet	F acc. to IEC/EN 60320-2-2, UL 498 CSA C22.2 no. 42 (for cold conditions) pin-temperature 70 °C, 10A, Protection Class 1
------------------	--

Dimensions

Quadbloc + Two 4758

Cut-out for 2 mm Snap-in Inlet



Panel cut-out 134 x 32,5 mm, corner radius max. 5 mm
 With power entry module, type 6200 or type 6220

Variants
[Distributor-Stock-Check](#) | [SCHURTER-Stock-Check](#) | [e-Store](#)

Panel Thickness s [mm]	Terminal	Length [mm]	Order Number
1	Quick connect terminals 6.3 x 0.8 mm	138	4758.3200
1.2	Quick connect terminals 6.3 x 0.8 mm	138	4758.8200
1.5	Quick connect terminals 6.3 x 0.8 mm	138	4758.4200
2	Quick connect terminals 6.3 x 0.8 mm	138	4758.5200
2.5	Quick connect terminals 6.3 x 0.8 mm	138	4758.6200
3	Quick connect terminals 6.3 x 0.8 mm	138	4758.7200
1	Solder terminals 4 x 0.8 mm	138	4758.3400
1.2	Solder terminals 4 x 0.8 mm	138	4758.8400
1.5	Solder terminals 4 x 0.8 mm	138	4758.4400
2	Solder terminals 4 x 0.8 mm	138	4758.5400
2.5	Solder terminals 4 x 0.8 mm	138	4758.6400
3	Solder terminals 4 x 0.8 mm	138	4758.7400
1	Solder terminals 4 x 0.8 mm and quick connect terminals 6.3 x 0.8 mm	138	4758.3000
1.2	Solder terminals 4 x 0.8 mm and quick connect terminals 6.3 x 0.8 mm	138	4758.8000
1.5	Solder terminals 4 x 0.8 mm and quick connect terminals 6.3 x 0.8 mm	138	4758.4000
2	Solder terminals 4 x 0.8 mm and quick connect terminals 6.3 x 0.8 mm	138	4758.5000
2.5	Solder terminals 4 x 0.8 mm and quick connect terminals 6.3 x 0.8 mm	138	4758.6000
3	Solder terminals 4 x 0.8 mm and quick connect terminals 6.3 x 0.8 mm	138	4758.7000

Please note, all quadblobs are available in protection-class II upon request.

Cord retaining clamp see accessories

Packaging unit 50 Pcs

Required Accessory

Description



6200
IEC Appliance Inlet C14 with Fuseholder 1-pole

IP 40, 5 x 20, 1-pole	6200.4120
IP 40, 5 x 20, 1-pole	6200.4220
IP 40, 5 x 20, 1-pole	6200.4320



6220
IEC Appliance Inlet C14 with Fuseholder 2-pole

IP 40, 5 x 20, 2-pole	6220.5120
IP 40, 5 x 20, 2-pole	6220.5220
IP 40, 5 x 20, 2-pole	6220.5320

Accessories

Cord retaining kits
Cord retaining strain relief



Flat head, Z	0888.0021
Flat head, E	4700.0005
Flat head, G	4700.0007
Flat head, H	4700.0008

Mating Inlets/Plugs

Category / Description

Interconnection Cord Overview complete



Interconnection Cord with IEC Plug E, Angled	0607
Interconnection Cord with IEC Plug E, Angled	0608
Interconnection Cord with IEC Plug E, Straight	0609
Interconnection Cord with IEC Plug G, Angled	607B
Interconnection Cord with IEC Plug G, Angled	608B
Interconnection Cord further types to 4758	...

Plug Overview complete



IEC Plug E, Cord Connector (Rewireable), Straight, max. cable Diameter 8.5 mm	4732
IEC Plug E, Cord Connector (Rewireable), Angled, max. Cable Diameter 10 mm	4733
IEC Plug E, Cord Connector (Rewireable), Straight, max. Cable Diameter 10 mm	4735
IEC Plug E, Cord Connector (Rewireable), Angled, max. Cable Diameter 10 mm	4736
IEC Plug E, Cord Connector (Rewireable), Straight	9009
Plug further types to 4758	...