

"High Frequency Ceramic Solutions"

2.45 GHz Antenna (Vertical Orientation)

P/N 2450AT45A100

Detail Specification: 07/10/09

Page 1 of 9

General Specifications

Part Number	2450AT45A100
Frequency Range	2400 - 2500 Mhz
Peak Gain	3.0 dBi typ. (XZ-V)
Average Gain	1.0 dBi typ. (XZ-V)
Return Loss	9.5 dB min.

Input Power	3W max.
Impedance	50 Ω
Operating Temperature	-40 to +85°C
Reel Quantity	1,000

Mechanical Dimensions

	In	mm
L	0.374 ± 0.008	9.50 ± 0.20
W	0.079 ± 0.008	2.00 ± 0.20
T	0.047 +.004/-.008	1.20 +0.1/-0.2
a	0.020 ± 0.012	0.50 ± 0.30


Terminal Configuration

No.	Function
1	Feeding Point
2	NC


Mounting Considerations

Mount these devices with brown mark facing up. Units: mm

* Line width should be designed to provide 50Ω impedance matching characteristics.



a) Without Matching Circuit (moderate bandwidth)



b) With Matching Circuit* (wide bandwidth)

*matching circuit and component values will depend on PCB layout.

JTI P/N for Matching Circuit:
Cap (1.5pF): 500R07S1R5BV4T
Inductor (3.9nH): L-07C3N9SV6T

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

"High Frequency Ceramic Solutions"


2.45 GHz Antenna (Vertical Orientation)

P/N 2450AT45A100

Detail Specification: 07/10/09

Page 2 of 9

Typical Electrical Characteristics (T=25°C)



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.

"High Frequency Ceramic Solutions"


2.45 GHz Antenna (Vertical Orientation)

P/N 2450AT45A100

Detail Specification: 07/10/09

Page 3 of 9

Typical Radiation Patterns



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2009 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz Antenna (Horizontal Orientation_1)

P/N 2450AT45A100

Detail Specification: 07/10/09


Page 4 of 9

General Specifications

Part Number	2450AT45A100
Frequency Range	2400 - 2500 Mhz
Peak Gain	1.5 dBi typ. (XZ-V)
Average Gain	0.0 dBi typ. (XZ-V)
Return Loss	9.5 dB min.


Mechanical Dimensions

	In	mm
L	0.374 ± 0.008	9.50 ± 0.20
W	0.079 ± 0.008	2.00 ± 0.20
T	0.047 +.004/-.008	1.20 +0.1/-0.2
a	0.020 ± 0.012	0.50 ± 0.30



Terminal Configuration


No.	Function
1	Feeding Point
2	NC



Mounting Considerations

Mount these devices with brown mark facing up. Units: mm

* Line width should be designed to provide 50Ω impedance matching characteristics.



*matching circuit and component values will depend on PCB layout.

JTI P/N for Matching Circuit:
Cap (1.5pF): 500R07S1R5BV4T

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

"High Frequency Ceramic Solutions"

2.45 GHz Antenna (Horizontal Orientation)

P/N 2450AT45A100


Detail Specification: 07/10/09

Page 5 of 9

Typical Electrical Characteristics (T=25°C)



Test Board

EVB p/n:
2450AT45A100-EB2SMA



Return Loss

a) With Matching Circuit



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.


"High Frequency Ceramic Solutions"

2.45 GHz Antenna (Horizontal Orientation)

P/N 2450AT45A100

Detail Specification: 07/10/09

Page 6 of 9



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com
 4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2009 Johanson Technology, Inc. All Rights Reserved

"High Frequency Ceramic Solutions"

2.45 GHz Antenna (Horizontal Orientation_2)

P/N 2450AT45A100

Detail Specification: 07/10/09


Page 7 of 9

General Specifications

Part Number	2450AT45A100
Frequency Range	2400 - 2500 Mhz
Peak Gain	1.3 dBi typ. (XZ-V)
Average Gain	0.6 dBi typ. (XZ-V)
Return Loss	9.5 dB min.


Mechanical Dimensions

	In	mm
L	0.374 ± 0.008	9.50 ± 0.20
W	0.079 ± 0.008	2.00 ± 0.20
T	0.047 +.004/-0.008	1.20 +0.1/-0.2
a	0.020 ± 0.012	0.50 ± 0.30



Terminal Configuration


No.	Function
1	Feeding Point
2	NC



Mounting Considerations

Mount these devices with brown mark facing up. Units: mm

* Line width should be designed to provide 50Ω impedance matching characteristics.



*matching circuit and component values will depend on PCB layout.

Johanson Technology, Inc. reserves the right to make design changes without notice.
All sales are subject to Johanson Technology, Inc. terms and conditions.

"High Frequency Ceramic Solutions"


2.45 GHz Antenna (Horizontal Orientation)

P/N 2450AT45A100

Detail Specification: 07/10/09

Page 8 of 9

Typical Electrical Characteristics (T=25°C)



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2009 Johanson Technology, Inc. All Rights Reserved


"High Frequency Ceramic Solutions"

2.45 GHz Antenna (Horizontal Orientation)

P/N 2450AT45A100

Detail Specification: 07/10/09

Page 9 of 9



Johanson Technology, Inc. reserves the right to make design changes without notice.

All sales are subject to Johanson Technology, Inc. terms and conditions.



www.johansontechnology.com

4001 Calle Tecate • Camarillo, CA 93012 • TEL 805.389.1166 FAX 805.389.1821

2009 Johanson Technology, Inc. All Rights Reserved