

**HIGH EFFICIENCY RECTIFIER**

**VOLTAGE RANGE 50 to 400 Volts CURRENT 8.0 Amperes**

**FEATURES**

- \* Low switching noise
- \* Low forward voltage drop
- \* Low thermal resistance
- \* High current capability
- \* High fast switching capability
- \* High surge capability


**MECHANICAL DATA**

- \* Case: D-PAK molded plastic
- \* Epoxy: Device has UL flammability classification 94V-0
- \* Lead: MIL-STD-202E method 208C guaranteed
- \* Mounting position: Any
- \* Weight: 0.33 grams

NEW RELEASE

**MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS**

Ratings at 25 °C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%.



MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)


RATINGS	SYMBOL	HER801K	HER802K	HER803K	HER804K	HER805K	UNITS
Maximum Recurrent Peak Reverse Voltage	V <sub>RRM</sub>	50	100	200	300	400	Volts
Maximum RMS Voltage	V <sub>RMS</sub>	35	70	140	210	280	Volts
Maximum DC Blocking Voltage	V <sub>DC</sub>	50	100	200	300	400	Volts
Maximum Average Forward Rectified Current at T <sub>A</sub> = 75 °C	I <sub>O</sub>	8.0					Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I <sub>FSM</sub>	200					Amps
Typical Thermal Resistance (Note 1)	R <sub>θJC</sub>	2.5					°C/W
	R <sub>θJA</sub>	30					
Typical Junction Capacitance (Note 2)	C <sub>J</sub>	40					pF
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to + 150					°C

ELECTRICAL CHARACTERISTICS (@TA=25 °C unless otherwise noted)


CHARACTERISTICS	SYMBOL	HER801K	HER802K	HER803K	HER804K	HER805K	UNITS
Maximum Instantaneous Forward Voltage at 8.0A DC	V <sub>F</sub>	1.0			1.3		Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	@T <sub>A</sub> = 25°C	2					uAmps
	@T <sub>A</sub> = 100°C	150					
Maximum Reverse Recovery Time (Note 3)	t <sub>rr</sub>	50					nSec

- NOTES : 1. Thermal Resistance : Heat-sink case mounted or if PCB mounted.  
2. Measured at 1 MHz and applied reverse voltage of 4.0 volts.□  
3. Test Conditions: I<sub>F</sub>= 0.5A, I<sub>R</sub>= -1.0A, I<sub>RR</sub>= -0.25A.  
4. "Fully ROHS compliant", "100% Sn plating (Pb-free)".  
5. Suffix "R" for Reverse Polarity.  
6. Suffix "S" for D2-PAK Pkg.


# RATING AND CHARACTERISTICS CURVES ( HER801K THRU HER805K )




**FIG.1 TYPICAL FORWARD CURRENT DERATING CURVE**




**FIG.2 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS**



**FIG.3 TYPICAL REVERSE CHARACTERISTICS**



**FIG.4 TYPICAL JUNCTION CAPACITANCE**



**FIG.5 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT**

## DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.