QC M8*1.0

Liquid Glue

O-Ring

QC 6.84 +0.00 -0.10

QC 6.90

35.0(REF.)

QC 20.0

5.50

ø10.5

Shrink Tube

+

−

Shrink Tube

LED Assembly

Nut

Material:
- Waterproof Rate: IP67
- LED Holder: Brass, Nickel plating
- LED: ø5MM, Red
- Lense Color: Water Clear
- Forward Voltage: Red Typ. 2.2V/Max.2.4V
- Forward Current: Red Max. 30mA
- Luminous Intensity: Red Typ.5,000(Mcd)
- Reverse Voltage: 5V DC
- Gasket: EPDM, Black
- Screw Nut: Brass, Nickel plating
- Operating Temperature: -40°C~+80°C
- For Panel Thickness 6.5MM Max.

QC Quality Control: Important Dimension to check

Unit: MM±0.25MM

7.1±0.1

ø8.2±0.1

Recommended Panel Cut-Out

Ⓐ = Assmann logo

RoHS Compliant

ITEM NO.

A-LED8-1RBAS-MR7-1-R

TITLE   Waterproof LED - Red color, M8 size connector,
ø5MM, Metal housing, Solder pins, IP67 unmated

ASSMANN
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com