		Approximate Dimensions—	
Description		mm (inches)	Catalogue Number
	Stainless Steel Weatherproof Keys	50 (1.96) 17 (0.66) Standard Key	440T-AKEYE10⊗
1000	Stainless Steel Weatherproof Dust Cap	39 (1.54) 16 (0.63)	440T-ASFC10⊗
	Stainless Steel Weatherproof Dust Cap for Switchgear Adaptor	16 (0.63)	440T-ASFC11 <b>0</b>
	Stainless Steel Replacement Code Barrel for 100A Rotary Switch	42 (1.65) 23 (0.91) 2 Fixing Holes 4.5 (0.18) Dia	440T-ASCBE11 <b>0</b>
	Stainless Steel Replacement Code Barrels for Products Other than 100A RPS/RKS Units	2 Fixing Hofes 32 (1.26) 4.5 (0.18) Dia	440T-ASCBE14 <b>0</b>

◆ Substitute the desired primary code for this symbol (key not included). See page 5-6 for code selection.
◆ Substitute the desired code for this symbol. See page 5-6 for code selection.



**Product Selection** 

**ATTENTION:** The presence of spare keys, override keys, or spare actuators can compromise the integrity of safety interlocking systems. Personal injury or death, property damage or economic loss can result from the introduction of spare keys, override keys or spare actuators into interlocking systems without appropriate management controls, working procedures and alternative protective measures to control their use and availability.