

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0850033495](#)
Status: **Active**
Overview: [din_41612](#)
Description: 2.54mm (.100") Pitch DIN 41612 C Style Male Header, Right Angle, Through Hole, 0.60µm (24µ") Selective Gold (Au) Plating, 64 Circuits, without Mounting Clips, No Flux Proof, Lead free

Documents:

[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)
[Product Specification PS-85003-0001 \(PDF\)](#)

Agency Certification

CSA LR19980
 UL E29179

General

Product Family Backplane Connectors
 Series [85003](#)
 Application Backplane
 Comments No Mounting Clips. No Flux Proof. 5.4mm(.213") First-Mate-Last-BreakContacts. 4.8mm(.189") Normal Contacts
 Component Type PCB Header
 Overview [din_41612](#)
 Product Name IEC 603-2/DIN 41612
 Style C

Physical

Circuits (Loaded) 64
 Circuits (maximum) 96
 Circuits Detail Standard Contacts at: A:a1-a16,a19-a32; C:c1-c7,c9-c13,c15,c16,c18,c20- c25,c27-c32. First-Mate-Last-Break Contacts at: X:c8,c14,c17,c19,c26; Z:a17,a18
 Color - Resin Gray
 Durability (mating cycles max) 400
 First Mate / Last Break Yes
 Flammability 94V-0
 Guide to Mating Part No
 Keying to Mating Part Yes
 Material - Metal Brass
 Material - Plating Mating Gold
 Material - Plating Termination Tin
 Material - Resin Polyester
 Number of Columns 16
 Number of Pairs Open Pin Field
 Number of Rows 3
 Orientation Right Angle
 PC Tail Length (in) 0.118 In
 PC Tail Length (mm) 3.00 mm
 PCB Locator No
 PCB Retention Yes
 PCB Thickness Recommended (in) 0.062 In
 PCB Thickness Recommended (mm) 1.60 mm
 Packaging Type Carton
 Pitch - Mating Interface (in) 0.100 In
 Pitch - Mating Interface (mm) 2.54 mm

EU RoHS
ELV and RoHS
Compliant
REACH SVHC
 Not Reviewed
Halogen-Free
Status
Not Reviewed

China RoHS



Need more information on product environmental compliance?

Email productcompliance@molex.com
 For a multiple part number RoHS Certificate of Compliance, [click here](#)

Please visit the [Contact Us](#) section for any non-product compliance questions.

Search Parts in this Series
[85003Series](#)

Pitch - Term. Interface (in)	0.100 In
Pitch - Term. Interface (mm)	2.54 mm
Plating min: Mating (µin)	24
Plating min: Mating (µm)	0.60
Plating min: Termination (µin)	98
Plating min: Termination (µm)	2.5
Polarized to PCB	Yes
Stackable	No
Surface Mount Compatible (SMC)	No
Temperature Range - Operating	-55°C to +125°C
Termination Interface: Style	Through Hole

Electrical

Current - Maximum per Contact	1A
Data Rate	622.0 Mbps
Voltage - Maximum	250V AC (RMS)

Solder Process Data

Duration at Max. Process Temperature (seconds)	10
Lead-free Process Capability	Wave Capable (TH only)
Process Temperature max. C	260

Material Info

Reference - Drawing Numbers

Product Specification	PS-85003-0001
Sales Drawing	SD-85003-3495

This document was generated on 05/17/2010

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

20 19 18 17 16 15 14 13 12 11 9 8 7 6 5 4 3 2 1

VIEW ON MATING SIDE

φ	C	C	C	C	C	C	X	C	C	C	C	C	X	C	X	C	C	X	C	C	C	C	C	C	C	C	C	C	C	C		
φ	A	A	A	A	A	A	A	A	A	A	A	A	Z	Z	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A		
	32	31	30	29	28	27	26	25	24	23	22	21	20	19	18	17	16	15	14	13	12	11	10	9	8	7	6	5	4	3	2	—

A = 30 STANDARD CONTACTS L = 3
 C = 27 STANDARD CONTACTS L = 3
 Z = 2 FMLB CONTACTS +0.6 L = 3
 X = 5 FMLB CONTACTS +0.6 L = 3
 S = 64 TOTAL NUMBER OF CONTACTS

MARKING	STANDARD
PERFORMANCE LEVEL	G2/O = CONTACT AREA LEVEL2 / TERMINATION TIN
FLUX PROOF	NO
FIXING CLIP	NO
DIMENSIONS	SD-85003-0001 SHT 1

X	G2/O	c8, 14, 17, 19, 26
Z	G2/O	φ17, 18
C	G2/O	c1-7, 9-13, 15, 16, 18, 20-25, 27-32
A	G2/O	φ1-16, 19-32
CONTACT SYMBOL	PERFORMANCE LEVEL	CONTACT POSITION NUMBER

EC NO. I 2004-XXXX DRAWN S. 09/09/03 CHK'd G.L. 09/09/03 APPROV'd L. 09/09/03	QUALITY SYMBOLS MAJOR CRITICAL	GENERAL TOLERANCES: (UNLESS SPECIFIED) <table border="1"> <tr> <th colspan="2">mm</th> <th colspan="2">INCH</th> </tr> <tr> <td>4 PLACES</td> <td>± 0.1</td> <td colspan="2">\pm</td> </tr> <tr> <td>3 PLACES</td> <td>± 0.1</td> <td colspan="2">\pm</td> </tr> <tr> <td>2 PLACES</td> <td>± 0.1</td> <td colspan="2">\pm</td> </tr> <tr> <td>1 PLACE</td> <td>± 0.1</td> <td colspan="2">\pm</td> </tr> </table>	mm		INCH		4 PLACES	± 0.1	\pm		3 PLACES	± 0.1	\pm		2 PLACES	± 0.1	\pm		1 PLACE	± 0.1	\pm		SCALE <input checked="" type="checkbox"/> MM <input type="checkbox"/> INCH	DESIGN UNITS <input checked="" type="checkbox"/> MM <input type="checkbox"/> INCH	THIRD ANGLE PROJECTION <input checked="" type="checkbox"/> THIRD ANGLE	DIMENSIONS: <input type="checkbox"/> MM <input type="checkbox"/> INCH <input checked="" type="checkbox"/> INCH ONLY <input type="checkbox"/> INCH ONLY	SHT 1 REV
			mm		INCH																						
4 PLACES	± 0.1	\pm																									
3 PLACES	± 0.1	\pm																									
2 PLACES	± 0.1	\pm																									
1 PLACE	± 0.1	\pm																									
REV	DESCRIPTION	DRAWN BY & DATE S.S. 20/04/01	CHECKED BY & DATE G.L. 20/04/01	APPROVED BY & DATE G.L. 20/04/01	TITLE: 96 POS MALE CONNECTOR ACCORDING DIN 41612 STYLE C CONTACTS ARRANGEMENT	MATERIAL NO. 85003-3495	DRAWING NO. SD-85003-3495	SHEET NO. 1 OF 1																			
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		CAD FILENAME SD-85003-3495.S01	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.		MOLEX INCORPORATED			SIZE D																			

19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1