

Product SKU: C2003.21.01

Product Description: (C2003) Hook-Up Wire, 24 AWG Solid Tinned Copper, PVC Insulation, Black - 1000 Ft.

Spool

Product Category: Electronics - Hook-Up Wire - UL 1007, UL 1569, CSA TR-64 - SOLID CONDUCTORS -

Black



Product Construction:

Conductor: • Fully-annealed, tinned copper per ASTM B-33

Insulation: • Color Code: See chart below

Premium grade color-coded PVC

• Temperature range: $-20\hat{A}^{\circ}C$ to $+105\hat{A}^{\circ}C$

Product Specification:

Conductor Size (AWG): • 24

Conductor/Strands: • Solid

No. of Pairs: • 1

Jacket Color: • Black

Nominal Insulation Thickness

(in):

• 0.016

Nominal Insulation Thickness

(mm):

• 0.40

Nominal Outside Diameter (in): • 0.052

Nominal Outside Diameter

(mm):

• 1.32

Standard Packaging: • 1000' Spool

Standard Package Quantity: • 1

UPC #:	• 079407765003
Put-up:	• 1000
SCC-14:	• 50079407765000
Cube:	• 216.72
Weight Per Unit of Measure:	• .0027
ColorOption:	• Black
Product Information:	
Applications:	• Internal wiring of electrical and electronic equipment
	• Internal wiring of panels and meters
	Point-to-point wiring
	• Suggested voltage rating: 300 Volts
Compliances:	• CSA TR-64 - 90°C, 300V
	 Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1007 - 80°C, 300V
	• UL Style 1569 - 105°C, 300V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305m) Spools
	Other put-ups available- consult Customer Service
Reference Charts	
Color Code Chart	
Technical Specifications	
<u>Unit Conversion Factors</u>	
Cable Design Equations - Balanced Pair	
Insulation and Jacket Properties The second	
Temperature Conversion Chart Desimal and Unit Conversion Factors	
Decimal and Unit Conversion Factors Cable Design Equations - Braid Shield	
Cable Design Equations - Coaxial Cable	
Cable Design Equations - Braid Shield AWG Conductor Chart Conduit Capacity Chart Cable Design Equations - Coaxial Cable	

Engineering Prefixes Coax Connector Cross Reference Glossary





Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

