

W2S130 Series

Tubeaxial

150Øx55mm



- AC fans with external rotor shaded-pole motor. Impedance protected against overloading.
- Die-cast aluminum housing. Impeller of sheet-steel, directly welded onto rotor.
- Rotational direction CCW looking at rotor.
- Mounting from either face using two 4.5 mm holes.
- Electrical connection via 2 spade terminals.
- Cable length 330 mm.
- Mounting from either face using 2 4.3 mm (.169") holes.
- UL, CSA, VDE approvals on some models, please contact application engineering.

Part Number	Curve	CFM @ 0	VAC	Hertz	Power (W)	dBA	Max Amb. Temp C	Bearing Type	Features	Wgt. (lbs)
W2S130-AA25-01	1	225	115	50/60	38	52	80	Ball	Leads	2.44
W2S130-AA25-44	1	225	115	50/60	38	52	80	Ball	Terminals	2.44
W2S130-AA25-51	1	225	115	50/60	38	52	80	Ball	Terminals	2.44
W2S130-BM15-01	2	263	115	50/60	46	60	70	Ball	Leads	2.44
W2S130-AA03-01	1	225	230	50/60	39	52	70	Ball	Leads	2.63
W2S130-AA03-44	1	225	230	50/60	38	52	70	Ball	Terminals	2.63
W2S130-AA03-51	1	225	230	50/60	38	52	70	Ball	Terminals	2.63
W2S130-BM03-01	2	250	230	50/60	46	60	70	Ball	Leads	2.44
W2S130-AA03-49	1	225	115/230	50/60	38	52	70	Ball	Leads	2.63

Fan Type	Air Flow
W2S130-AA	Exhaust over struts
W2S130-BM	Intake over struts

