

SEMiX252GB126HDs



SEMiX[®]2s

Trench IGBT Modules

SEMiX252GB126HDs

Preliminary Data

Features


- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability
- UL recognised file no. E63532

Typical Applications

- AC inverter drives
- UPS
- Electronic Welding

Remarks

- Case temperatur limited to $T_C=125^\circ\text{C}$ max.
- Not for new design



GB

Absolute Maximum Ratings					
Symbol	Conditions		Values	Unit	
IGBT					
V_{CES}			1200	V	
I_C	$T_j = 150^\circ\text{C}$	$T_c = 25^\circ\text{C}$	242	A	
		$T_c = 80^\circ\text{C}$	170	A	
I_{Cnom}			150	A	
I_{CRM}	$I_{CRM} = 2 \times I_{Cnom}$		300	A	
V_{GES}			-20 ... 20	V	
t_{psc}	$V_{CC} = 600\text{ V}$ $V_{GE} \leq 20\text{ V}$ $T_j = 125^\circ\text{C}$ $V_{CES} \leq 1200\text{ V}$			10	μs
T_j			-40 ... 150	$^\circ\text{C}$	
Inverse diode					
I_F	$T_j = 150^\circ\text{C}$	$T_c = 25^\circ\text{C}$	228	A	
		$T_c = 80^\circ\text{C}$	158	A	
I_{Fnom}			150	A	
I_{FRM}	$I_{FRM} = 2 \times I_{Fnom}$		300	A	
I_{FSM}	$t_p = 10\text{ ms, sin } 180^\circ, T_j = 25^\circ\text{C}$		1000	A	
T_j			-40 ... 150	$^\circ\text{C}$	
Module					
$I_{t(RMS)}$			600	A	
T_{stg}			-40 ... 125	$^\circ\text{C}$	
V_{isol}	AC sinus 50Hz, $t = 1\text{ min}$		4000	V	

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
IGBT						
$V_{CE(sat)}$	$I_C = 150\text{ A}$ $V_{GE} = 15\text{ V}$ chiplevel	$T_j = 25^\circ\text{C}$		1.7	2.1	V
		$T_j = 125^\circ\text{C}$		2.00	2.45	V
V_{CE0}			$T_j = 25^\circ\text{C}$	1	1.2	V
			$T_j = 125^\circ\text{C}$	0.9	1.1	V
r_{CE}	$V_{GE} = 15\text{ V}$		$T_j = 25^\circ\text{C}$	4.7	6.0	$\text{m}\Omega$
			$T_j = 125^\circ\text{C}$	7.3	9.0	$\text{m}\Omega$
$V_{GE(th)}$	$V_{GE}=V_{CE}, I_C = 6\text{ mA}$		5	5.8	6.5	V
I_{CES}	$V_{GE} = 0\text{ V}$ $V_{CE} = 1200\text{ V}$	$T_j = 25^\circ\text{C}$		0.1	0.3	mA
		$T_j = 125^\circ\text{C}$				mA
C_{ies}	$V_{CE} = 25\text{ V}$ $V_{GE} = 0\text{ V}$		$f = 1\text{ MHz}$		10.7	nF
C_{oes}			$f = 1\text{ MHz}$		0.56	nF
C_{res}			$f = 1\text{ MHz}$		0.48	nF
Q_G	$V_{GE} = -8\text{ V...} + 15\text{ V}$				1200	nC
R_{Gint}	$T_j = 25^\circ\text{C}$				5.00	Ω
$t_{d(on)}$	$V_{CC} = 600\text{ V}$				300	ns
t_r	$I_C = 150\text{ A}$ $T_j = 125^\circ\text{C}$				45	ns
E_{on}	$R_{G\ on} = 3\ \Omega$				20	mJ
$t_{d(off)}$	$R_{G\ off} = 3\ \Omega$				570	ns
t_f					110	ns
E_{off}					21	mJ
$R_{th(j-c)}$	per IGBT				0.15	K/W
$R_{th(j-s)}$	per IGBT					K/W

SEMiX252GB126HDs



SEMiX[®]2s

Trench IGBT Modules

SEMiX252GB126HDs

Preliminary Data

Features

- Homogeneous Si
- Trench = Trenchgate technology
- $V_{CE(sat)}$ with positive temperature coefficient
- High short circuit capability
- UL recognised file no. E63532


Typical Applications

- AC inverter drives
- UPS
- Electronic Welding

Remarks

- Case temperatur limited to $T_C=125^\circ\text{C}$ max.
- Not for new design

Characteristics						
Symbol	Conditions		min.	typ.	max.	Unit
Inverse diode						
$V_F = V_{EC}$	$I_F = 150\text{ A}$ $V_{GE} = 0\text{ V}$ chipelevel	$T_j = 25^\circ\text{C}$		1.6	1.8	V
		$T_j = 125^\circ\text{C}$		1.6	1.8	V
V_{F0}		$T_j = 25^\circ\text{C}$	0.9	1	1.1	V
		$T_j = 125^\circ\text{C}$	0.7	0.8	0.9	V
r_F		$T_j = 25^\circ\text{C}$	3.3	4.0	4.7	m Ω
		$T_j = 125^\circ\text{C}$	4.7	5.3	6.0	m Ω
I_{RRM}	$I_F = 150\text{ A}$	$T_j = 125^\circ\text{C}$		260		A
Q_{rr}	$di/dt_{off} = 4600\text{ A}/\mu\text{s}$ $V_{GE} = -15\text{ V}$	$T_j = 125^\circ\text{C}$		43		μC
E_{rr}	$V_{CC} = 600\text{ V}$	$T_j = 125^\circ\text{C}$		18		mJ
$R_{th(j-c)}$	per diode				0.24	K/W
$R_{th(j-s)}$	per diode					K/W
Module						
L_{CE}				18		nH
$R_{CC'+EE'}$	res., terminal-chip	$T_C = 25^\circ\text{C}$		0.7		m Ω
		$T_C = 125^\circ\text{C}$		1		m Ω
$R_{th(c-s)}$	per module			0.045		K/W
M_s	to heat sink (M5)		3		5	Nm
M_t	to terminals (M6)		2.5		5	Nm
						Nm
w					250	g
Temperature sensor						
R_{100}	$T_C=100^\circ\text{C}$ ($R_{25}=5\text{ k}\Omega$)			0,493 $\pm 5\%$		k Ω
$B_{100/125}$	$R_{(T)}=R_{100}\exp[B_{100/125}(1/T-1/T_{100})]$; $T[\text{K}]$;			3550 $\pm 2\%$		K



GB




Fig. 1 Typ. output characteristic, inclusive $R_{CC'+EE'}$




Fig. 2 Rated current vs. temperature $I_C = f(T_C)$




Fig. 3 Typ. turn-on /-off energy = $f(I_C)$




Fig. 4 Typ. turn-on /-off energy = $f(R_G)$




Fig. 5 Typ. transfer characteristic












Fig. 6 Typ. gate charge characteristic




SEMiX252GB126HDs

case: SEMiX 2s

screw duct (4x):
A-A (2 : 1)




All measures in Z-direction
valid as mounted to heat sink



* all measures with $\pm 0,2$ B C

Rules for the contact PCB:
- holes guidepins = $\varnothing 4 \pm 0,1$
- spring landing pad = $\varnothing 3,5 \pm 0,2$

SEMiX 2s



GB

This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, Chapter IX

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.