



NOTES:

- |                              |                     |
|------------------------------|---------------------|
| 1. DISPLAY TYPE:             | TN MODE             |
| 2. VIEWING DIRECTION:        | 6' 00               |
| 3. POLARIZER MODE:           | REFLECTIVE/POSITIVE |
| 4. OPERATING TEMP:           | 10°C--+35°C         |
| 5. STORAGE TEMP:             | -10°C--+60°C        |
| 6. VDD:                      | 3.3V                |
| 7. LCD OPERATING VOLTAGE:    | 3.3V                |
| 8. DRIVE METHOD:             | DUTY 1/2 BIAS 1/2   |
| 9. CONTROLLER:               | HT1621              |
| 10. ALL UNMARKED TOLERANCES: | ±0.3mm              |
| 11. WITHOUT BACKLIGHT        |                     |

1	2	3	4	5
VDD	VSS	DATA	WR	CS



**TIAN-MA MICROELECTRONICS CO.**

22/F., HANGDU Building, Shennan Road, Central, Shenzhen, China

<b>DRAWN BY:</b>	<b>TITLE:</b> TM0127AAA6	
<b>CHECKED BY:</b>	<b>DWG NO:</b> G-3	
<b>APPROVED BY:</b>	<b>DWG NAME:</b> TM0127AAA6G-3	<b>SCALE:</b>
<b>CONFIRMED BY:</b>	<b>SHREV NO:</b> 0F	<b>UNITS:</b> DIMED