



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date: Feb, 22, 2008

Product Name: SAW Filter 915 MHz SMD 3.0X3.0 mm

TST Parts No.: TA0829A

Customer Parts No.: _____

Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Bob Chau

Approval by: _____ Francis Chen

Date: _____ 2, 22, 2008



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 915MHz

MODEL NO.:TA0829A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -40°C to +60°C
4. Storage Temperature: -40°C to +85°C


RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Type.	Max.	Note
Center Frequency Fc	MHz	-	915	-	-
Insertion Loss (910 ~ 920 MHz) IL	dB	-	3	4	-
Amplitude Ripple (910 ~ 920 MHz)	dB	-	0.8	2	-
Attenuation (Reference level from 0 dB)					
D.C ~ 880 MHz	dB	45	50	-	-
880 ~ 890 MHz	dB	40	52	-	-
940 ~ 950 MHz	dB	35	40	-	-
950 ~ 1200 MHz	dB	43	48	-	-
1200 ~ 1600 MHz	dB	40	48	-	-
1600 ~ 2200 MHz	dB	30	43	-	-
2200 ~ 2500 MHz	dB	25	35	-	-
2500 ~ 3000 MHz	dB	20	27	-	-

C. MEASUREMENT CIRCUIT:

HP Network analyzer




D.OUTLINE DRAWING:





△ : Year Code (2006->6, ..., 2009->9)

□ : Date Code (Follow the table from planner each year)

E. PCB Footprint:




F. Frequency Characteristics :




Reflection Functions :

S11




S22




G. PACKING:

1. REEL DIMENSION

(Reel Count : 7"=1000 ; 13"=3000)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

