

PFS

HIGH EFFICIENCY RECTIFIER

HER501 THRU HER508	VOLTAGE RANGE	50 to 800 Volts
	CURRENT	5.0Ampere


DO-27

FEATURES

- Low coat construction
- Fast switching for high efficiency.
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:
260°C/10 secods/.375”(9.5mm)lead length at 5 lbs(2.3kg) tension

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.042ounce, 1.19 grams



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	HER 501	HER 502	HER 503	HER 504	HER 505	HER 506	HER 507	UNITS
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	50	100	200	300	400	600	800	Volts
Maximum RMS Voltage	V_{RMS}	35	70	140	210	280	420	560	Volts
Maximum DC Blocking Voltage	V_{DC}	50	100	200	300	400	600	800	Volts
Maximum Average Forward Rectified Current 0.375”(9.5mm) lead length at $T_A=50^\circ C$	$I_{(AV)}$	5.0							Amp
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	I_{FSM}	200					150		Amps
Maximum Instantaneous Forward Voltage @ 3.0A	V_F	1.0			1.3	1.5	1.7	Volts	
Maximum DC Reverse Current at Rated DC Blocking Voltage	$T_A=25^\circ C$	10							μA
	$T_A=125^\circ C$	500							
Maximum Full Load Recovery Current,full cycle average 0.375”(9.5mm)lead length at $T_L=55^\circ C$	$IR_{(AV)}$	150							μA
Maximum Reverse Recovery Time(NOTE 1)	t_{rr}	70					100		ns
Typical Thermal Resistance (NOTE 2)	C_J	70					50		PF
Typical Thermal Resistance(NOTE 3)	$R_{\theta JA}$	20							$^\circ C/W$
Operating Junction Temperature Range	T_J, T_{STG}	(-55 to +150)							$^\circ C$

Notes:

- 1 Test Condition: $I_F=0.5A, I_R=1.0A, I_{RR}=0.25A$
2. Measured at 1.0 MHz and applied reverse of 4.0 V
- 3 Thermal resistance from junction to ambient with .375”(9.5mm)lead length, P.C.B. mounted. .

RATING AND CHARACTERISTIC CURVES HER501 THRU HER507

FIG.1-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-TYPICAL JUNCTION CAPACITANCE





FIG. 6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC



NOTE: 1. Rise Time = 7ns max. Input Impedance = 1megohm, 22pF
2. Rise time = 10ns max. Source Impedance = 50 ohms