


### Silicon Variable Capacitance Diode

- For FM radio tuner with extended frequency band
- High tuning ratio at low supply voltage (car radio)
- Monolithic chip (common cathode) for perfect dual diode tracking
- Good linearity for C- V curve
- High figure of merit
- Pb-free (RoHS compliant) package<sup>1)</sup>
- Qualified according AEC Q101



### BB914



Type	Package	Configuration	$L_S$ (nH)	Marking
BB914	SOT23	common cathode	1.8	SM

**Maximum Ratings** at  $T_A = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Symbol	Value	Unit
Diode reverse voltage	$V_R$	18	V
Peak reverse voltage ( $R \geq 5\text{k}\Omega$ )	$V_{RM}$	20	
Forward current	$I_F$	50	mA
Operating temperature range	$T_{Op}$	-55 ... 125	°C
Storage temperature	$T_{Stg}$	-55 ... 150	

<sup>1</sup>Pb-containing package may be available upon special request


**Electrical Characteristics at  $T_A = 25^\circ\text{C}$ , unless otherwise specified**

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>DC Characteristics</b>					
Reverse current	$I_R$	-	-	-	nA
$V_R = 16\text{ V}$		-	-	20	
$V_R = 16\text{ V}, T_A = 85^\circ\text{C}$		-	-	200	
<b>AC Characteristics</b>					
Diode capacitance	$C_T$	-	-	-	pF
$V_R = 2\text{ V}, f = 1\text{ MHz}$		42.5	43.75	45	
$V_R = 8\text{ V}, f = 1\text{ MHz}$		17.6	18.7	19.75	
Capacitance ratio	$C_{T2}/C_{T8}$	2.28	2.34	2.42	
Capacitance matching <sup>1)</sup>	$\Delta C_T/C_T$	-	-	1.5	%
$V_R = 2\text{ V}, V_R = 8\text{ V}, f = 1\text{ MHz}$					
Series resistance	$r_S$	-	0.28	-	$\Omega$
$V_R = 2\text{ V}, f = 100\text{ MHz}$					

<sup>1</sup>For details please refer to Application Note 047.


**Diode capacitance  $C_T = f(V_R)$**

$f = 1\text{MHz}$




**Capacitance ratio  $C_{Tref}/C_T = f(V_R)$**

$f = 1\text{MHz}$




Package Outline




1) Lead width can be 0.6 max. in dambar area

Foot Print




Marking Layout (Example)



Standard Packing

Reel  $\varnothing$ 180 mm = 3.000 Pieces/Reel  
 Reel  $\varnothing$ 330 mm = 10.000 Pieces/Reel



Edition 2006-02-01  
Published by  
Infineon Technologies AG  
81726 München, Germany  
© Infineon Technologies AG 2007.  
All Rights Reserved.

### **Attention please!**

The information given in this dokument shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenheitsgarantie"). With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

### **Information**

For further information on technology, delivery terms and conditions and prices please contact your nearest Infineon Technologies Office ([www.infineon.com](http://www.infineon.com)).

### **Warnings**

Due to technical requirements components may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies Office.

Infineon Technologies Components may only be used in life-support devices or systems with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system, or to affect the safety or effectiveness of that device or system.

Life support devices or systems are intended to be implanted in the human body, or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.