

形 名	社 名	最 大 定 格							順 方 向 特 性			逆 方 向 特 性			t r r max				そ の 他 の 特 性 等	外 形	
		V _{RS} M	V _{RR} M	V _R	I _O	T条件	I _{FS} M	T条件	V _F max	測定条件		I _R max	測定条件		(ns)	測 定 条 件					
		(V)	(V)	(V)	(A)	(℃)	(A)	(℃)	(V)	I _F (A)	T(℃)	(mA)	V _R (V)	T(℃)		I _F (A)	I _R (A)	diF/dt (A/μs)			
S5S4	新電元	45	40		5	110C	100	125j	0.55	5	25C	5	40	25C	110	5		5			14
S5S4M	新電元	45	40		5	114C	100	125j	0.55	5		3.5	40	25C	110	5		5			272A
S15S4	新電元	45	40		15	98C	300	125j	0.55	15	25C	15	40		150	15		10	1SR71-40と同一		41
S15S6	新電元	65	60		15	96c	300	125j	0.67	15	25c	10	60	25c							41
S30S4A	新電元	45	40		30	97C	600	125j	0.55	30	25C	20	40	25c	200	30		20	1SR72-40と同一		42
S30S6	新電元	65	60		30	95c	600	125j	0.67	30	25c	20	60	25c							42
S60S4	新電元	45	40		60	83C	850	125j	0.58	60	25C	40	40		225	50		20	1SR73-40と同一		42
S60S6	新電元	65	60		60	82c	850	125j	0.67	60	25c	40	60	25c							42
SB05-03C	三洋		30		0.5		5		0.55	0.5		0.03	15		10	0.1			C=16pF		610A
SB05-03Q	三洋		30		0.5		3		0.55	0.5		0.03	15		10	0.1			C=16pF		205A
SB05-05CP	三洋	55	50		0.5		5		0.55	0.5		0.05	25		10	0.1	0.1		Ct=17pF		610A
SB05-05NP	三洋	55	50		0.5		5		0.55	0.5		0.05	25		10	0.1	0.1		Ct=18pF		730G
SB05-05P	三洋	55	50		0.5		5		0.55	0.5		0.05	25		10	0.1	0.1		Ct=18pF		237
SB05-09	三洋	95	90		0.5	60a	10		0.7	0.5		0.08	45		10	0.1	0.1		Ct=34pF		64
SB05-18M	三洋	190	180		0.5	26a	10	25j	0.85	0.5		0.06	90		20	0.1	0.1		Ct=45pF		64
SB07-03C	三洋	35	30		0.7		5		0.55	0.7		0.08	15		10	0.1	0.1		Ct=25pF		610A
SB07-03N	三洋	35	30		0.7		5		0.55	0.7		0.08	15		10	0.1	0.1		Ct=25pF		730G
SB07-03P	三洋	35	30		0.7		5		0.55	0.7		0.08	15		10	0.1	0.1		Ct=26pF		237
SB10-03A2	三洋	35	30		1	50a	40	25j	0.55	1		1	30		30	1		50			666
SB10-03A3	三洋	35	30		1	46a	40	25j	0.55	1		1	30		30	1		50			88E
SB10-04A3	三洋	45	40		1		30		0.55	1		0.8	40						ﾌﾟﾘﾝﾄ基板はんだｼｯﾄﾞ3mmφ		88F
SB10-05	三洋	55	50		1		10		0.55	1		0.08	25		10	0.1	0.1		Ct=52pF		64
SB10-05A2	三洋	55	50		1	33a	25	25j	0.58	1		1	50		30	1		50			666
SB10-05A3	三洋	55	50		1	29a	25	25j	0.58	1		1	50		30	1		50			88E
SB10-05PCP	三洋	55	50		1		10		0.55	1		0.08	25		10	0.1	0.1		Ct=52pF		237
SB10-09F	三洋	95	90		1	119c	10		0.7	1		0.4	45		20	0.1	0.1		Ct=70pF		243C
SB10-09P	三洋	95	90		1		5		0.7	1		0.2	45		20	0.1			C=70pF		237
SB11-04HP	三洋	45	40	0.85			30	25j	0.55	1.1		1	40						10は7Mﾏｲｸ基板実装時		485B
SB20-03B	三洋	35	30		2	113c	20		0.55	2		0.1	15		20	0.1	0.1		Ct=70pF		241C
SB20-03E	三洋	35	30		2	113c	20		0.55	2		0.1	15		20	0.1	0.1		Ct=70pF		242C
SB20-03P	三洋	35	30		2		20		0.55	2		0.1	15		20	0.1	0.1		Ct=70pF		237
SB20-05F	三洋	55	50		2	117c	20		0.55	2		0.7	25		20	0.3	0.3		Ct=120pF		243C
SB20-05P	三洋	55	50		2		10		0.55	2		0.2	25		20	0.3	0.3		C=120pF		237
SB20-05Z	三洋		50		2		20		0.55	2		0.2	25		20	0.3			C=120pF		563
SB30-03F	三洋	35	30		3	114c	30		0.55	3		0.7	15		30	0.3	0.3		Ct=160pF		243C
SB30-03P	三洋	35	30		3		10		0.55	3		0.2	15		30	0.3	0.3		10はﾍﾞﾐﾏｲｸ基板実装時		237
SB30-03Z	三洋	35	30		3		20		0.55	3		0.2	15		30	0.3	0.3				563
SB803-04	富士電機	48	40		2	105c	100	125j	0.55	2		5	40								486C
SB803-06	富士電機	60	60		2	105c	60	125j	0.58	2		5	60								486C
SB803-09	富士電機	90	90		2	105c	60	125j	0.9	2		2	90								486C
SC802-02	富士電機		20		1.5	112c	50	125j	0.47	1		1	20								60
SC802-4	富士電機	48	40		1	115L	40	125j	0.55	1		2	40								485G
SC802-6	富士電機	60	60		1	111L	30	125j	0.58	1		2	60								485G
SC802-9	富士電機	100	90		1	110L	30	125j	0.85	1		1	90								485G
SE014	富士電機	45	40		1		10	125j	0.55	1		2	40		50	0.1	0.1				237

